

# LVF-5003C-P2713 Varifocal lens, 2.7-13mm, 3MP, CS mount

www.boschsecurity.com



**BOSCH**

Invented for life



- ▶ High-quality optics
- ▶ Reliable, robust construction
- ▶ Focal length options

As surveillance cameras can now capture even higher picture resolutions through the use of HD sensor technology and advanced processing, the lenses also need to have an optical resolution that allows the camera to work at its optimal point.

This lens is designed to provide improved image resolution and sharpness, and better depth of field.

## System overview

This lens comes with a standard CS mount for use with a variety of cameras.

The P-iris control connection is a four-pin standard plug that fits directly into the camera's iris output. This lens delivers impressive optical quality due to its megapixel resolution, contrast reproduction, and coating.


The mechanical construction is designed to withstand both frequent iris control operations and the environmental stress of security installations. It provides long and reliable operation with no maintenance.

For flexible, high-quality, reliable lenses that match an HD camera's performance, this lens is the ideal solution.

## Certifications and approvals

| Region | Regulatory compliance/quality marks |                  |
|--------|-------------------------------------|------------------|
| Europe | CE                                  | BT-VS 2020-E-025 |

## Installation/configuration notes



4-pin iris connector

|        |                       |
|--------|-----------------------|
| Pin 1: | Damping coil -        |
| Pin 2: | Damping coil +        |
| Pin 3: | Driving coil + (open) |
| Pin 4: | Driving coil -        |

### Parts included

| Quantity | Component |
|----------|-----------|
| 1        | Unit      |

### Technical specifications

| LVF-5003C-P2713                     |  |
|-------------------------------------|--|
| Maximum sensor format               | 1/2.7-inch   |
| Optical resolution                  | 3 Megapixels   |
| Focal length                        | 2.7 - 13 mm  |
| Iris range                          | F1.4 to close  |
| Min object distance                 | 0.3 m (1 ft)   |
| Back focus distance (values in air) | 8 mm (0.315 in)  |
| Weight                              | 87 g (0.19 lb)   |
| Dimensions                          | Ø 47 mm (excluding focus and zoom knobs and iris block) x 75.11 mm |
| Lens mount                          | CS   |
| Angle of view (HxV)                 | 102 x 74° Wide   |

### LVF-5003C-P2713

|                     |                   |
|---------------------|-------------------|
| 1/3-inch sensor 4:3 | 22.4 x 16.9° Tele |
|---------------------|-------------------|

|   |                                     |
|---|-------------------------------------|
| Angle of view (HxV)<br>1/3-inch sensor 16:9 | 113 x 60° Wide<br>24.3 x 13.8° Tele |
|---|-------------------------------------|

|   |                                     |
|---|-------------------------------------|
| Angle of view (HxV)<br>1/2.7-inch sensor 16:9 | 126 x 66° Wide<br>26.7 x 15.2° Tele |
|---|-------------------------------------|

|   |                                     |
|---|-------------------------------------|
| Angle of view (HxV)<br>1/2.8-inch sensor 16:9 | 122 x 64° Wide<br>25.9 x 14.7° Tele |
|---|-------------------------------------|

|              |                       |
|--------------|-----------------------|
| Iris control | 4-pin, P-iris control |
|--------------|-----------------------|

|            |        |
|------------|--------|
| Focus ctrl | manual |
|------------|--------|

|           |        |
|-----------|--------|
| Zoom ctrl | manual |
|-----------|--------|

|              |     |
|--------------|-----|
| IR corrected | yes |
|--------------|-----|

### Environmental

|                         |                                  |
|-------------------------|----------------------------------|
| - Operating Temperature | -10°C to +50°C (+14°F to +122°F) |
|-------------------------|----------------------------------|

|                       |                                  |
|-----------------------|----------------------------------|
| - Storage Temperature | -40°C to +60°C (-40°F to +140°F) |
|-----------------------|----------------------------------|

|                      |                             |
|----------------------|-----------------------------|
| - Operating Humidity | Up to 60% RH non-condensing |
|----------------------|-----------------------------|

### Ordering information

#### LVF-5003C-P2713 Varifocal lens, 2.7-13mm, 3MP, CS mount

Varifocal P-iris megapixel IR corrected lens with 1/2.7 inch sensor and CS-mount

Order number **LVF-5003C-P2713**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia