

## DirectIP 16 Channel Decoder

# DD-1216

- Supports DirectIP™ NVR
- Supports IDIS IP Camera
- Supports HDMI, VGA, CVBS port
- Up to 480ips live display



## SPECIFICATIONS

| DECODER                 |                                                                                                                                                                           |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Compression       | H.264, H.265                                                                                                                                                              |
| Video Input             | 16ch IP                                                                                                                                                                   |
| Video Input Resolution  | Up to 12MP                                                                                                                                                                |
| Supported Devices       | DirectIP NVR, IDIS IP Camera                                                                                                                                              |
| Video Outputs           | 1 HDMI, 1 VGA, 1 CVBS                                                                                                                                                     |
| Display Resolution      | HDMI: 3840x2160, 2560x1440, 1920x1200, 1920x1080, 1680x1050, 1600x1200<br>VGA: 2560x1440, 1920x1200, 1920x1080, 1680x1050, 1600x1200<br>CVBS: 720x480(NTSC), 720x576(PAL) |
| Display Speed           | Up to 480ips                                                                                                                                                              |
| Max. Network Throughput | 90Mbps                                                                                                                                                                    |
| Network Connection      | Gigabit Ethernet x 1                                                                                                                                                      |
| GENERAL                 |                                                                                                                                                                           |
| Dimensions (W x H x D)  | 200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")                                                                                                                                 |
| Weight                  | 0.78kg (1.72lb)                                                                                                                                                           |
| Operation Temperature   | 0°C ~ 40°C (32°F ~ 104°F)                                                                                                                                                 |
| PoE (Class)             | Yes (IEEE 802.3af Class 0)                                                                                                                                                |
| Power Input             | 12VDC, PoE                                                                                                                                                                |
| Power Consumption       | 12V=, 1.03A, 12.7W<br>PoE, IEEE 802.3af(Class 3)                                                                                                                          |
| Approvals               | FCC, CE, KC                                                                                                                                                               |

## DIMENSIONS

(Unit - mm)

