

4000 Series Audio Modules

4000 Series “3+1” Audio Speaker Modules



Art. 4836-0



Art. 4836-1



Art. 4836-2



Art. 4836-0/M



Art. 4836-1/M



Art. 4836-1D/M



Art. 4836-2/M



Art. 4836-2D/M

Art.		4836-0	4836-1	4836-1D	4836-2	4836-2D
DESCRIPTION		Modular 4000 series “3+1” audio speaker (4K series audiokit range)				
BUTTONS	BUILT-IN	0	1	2	2	4
	MAX.	multiple combinations with the use of additional button modules: 4842, 4843, 4844, 4845, 4842D, 4843D, 4844D and 4845D				
FRONT FASCIA OPTIONS		Mirror Stainless Steel, /M Matt 316 Marine Grade Stainless Steel				
NAME PLATE & BACK LIGHT		No	Yes: 1 (backlit blue)		Yes: 2 (backlit blue)	
CALL PROGRESS LED’S		N/A				
MODULE PROGRAMMING		N/A				
MODULE SIZE		1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm				
ADJUSTMENT POTS		Yes: Microphone and Speaker				
NO. OF RELAYS		1 internal relay				
RELAY CONTACTS		Normally Open Contacts S/S1 (C/NO pair)				
RELAY VOLTAGE / AMPS		Dry Contact Voltage/Current Rating: 24Vac/dc 2A max.				
PTE INPUT		No				
WORKING VOLTAGE		13Vac (compatible PSU’s: 321 and 322)				
POWER CONSUMPTION		Stand-by: 25mA / During Call: 150mA / During Conversation: 70mA				
WORKING TEMP.		-10° to +50°C				