Pole & Tower Accessories ←

Stock items

TB Brackets & Fixed Camera Knuckles

• PTS-I Standard fixed camera knuckle

- o Load rating 10Kgs
- o General duty adjustable knuckle for mounting fixed cameras robust & economic

6xØ8.5 on a 101.6 PCD

Ø10mm stainless steel centre

pivot/locking bolt


M8 stainless

steel locking






PTS-I is fully adjustable rotates through 360 and tilts at 40 from horizon



HAS-


High specification fixed camera knuckle


- o Load rating 25Kgs
- O High specification adjustable knuckle where fine adjustment and a solid platform are required to ensure accurate reliable camera alignment





Filament plates give high friction locking capacity whilst allowing fine adjustment






Ø10mm stainless steel centre pivot/locking bolt

As standard, TB brackets are supplied with PTS-I knuckles. Brackets supplied with HAS-I knuckles fitted as option

• TB2-600F

Twin fixed



TB4-600F

Quadruple fixed

• TB3-600F Triple fixed

Knuckles mounted on TB bracket arms






PTS-I

HAS-I




Triple fixed manx




TB5-600F

Five way fixed




TB6-600F Six way fixed




• TB2-I000SF/SPT

Single fixed & PTZ




• TB2-1000

Twin PTZ



• TB3-600 SPT/TF

Twin fixed/single PTZ



All brackets for camera mounting have a Ø127 mounting plate with 8 no Ø8.5 equi - spaced on 101.6 PCD