


2N® INDOOR COMPACT


ANSWERING UNIT WITH INTUITIVE CONTROLS

The 2N® Indoor Compact is an indoor answering unit designed especially for the residential market. Installation by connecting a single UTP cable and configuration via a web interface guarantees that integrators can put the unit into operation quickly and easily. Users will be impressed by the minimalist design, tempered glass surface, 4.3" colour display and intuitive controls. A simply elegant solution for video communication.



- **Intuitive controls, even for inexperienced users**
- **Designer surface made of tempered glass**
- **Configuration via a web interface**
- **HD quality sound with noise suppression**
- **Switching video between internal and external cameras**
- **Backup of answering unit settings**

VARIANTS



BLACK

91378501



WHITE

91378501WH

TECHNICAL PARAMETERS

Power supply

Type	12 V / 1 A DC or PoE
PoE	802.3af
Reverse polarity protection	Yes

User interface

Controls	7 capacitive buttons with RGB LED backlighting
Operation	Press and hold the RESET button to restore factory settings, 3 LED status indicators

Audio

Microphone	Integrated
Speaker	Integrated, 2W
Induction loop output	600 mV RMS
Codecs	G.711, G.722, G.729, L16/16kHz

Video

Display	4.3" display, resolution 480 x 272 pixels
Codecs	H.263, H.264, MJPEG

Interface

LAN	10/100BaseT, RJ-45
Recommended cabling	Cat5e or higher

Doorbell Input

Input type	Switching contact (button/relay)
Contact type	Normally open (NO)
Contact parameters	Up to 50V/5mA, DC

Mechanical properties

Operating temperature	0 to 50°C
Storage temperature	-20 to 70°C
Relative operating humidity	10 to 90 % (non-condensing)
Recommended altitude	0 to 2000 m
Dimensions (W x H x D)	152 x 153 x 50mm
Weight	387g