

SMT-4343

43" LED Monitor



Key Feature

- Support up to 3840 x 2160 resolution
- Contrast ratio 800:1 (Min.), 1000:1 (Typ.)
- Fast response time 8ms (G to G)
- HDMI, DP, Audio connector
- Panel life 30,000 hours

Display		
Screen Size		42.5"
Max. Resolution		3840x2160
Brightness		300 cd/m ²
Contrast Ratio		800:1(Min)1000:1(Typ)
Aspect Ratio		16:09
Viewing Angle (H/V)		178°/178°
Display Color		1.07G (8bits + FRC)
Response Time		8ms(G to G)
Panel Life		30,000 hours
Interface		
HDMI	Connector	HDMI 1EA
	Available Format	640 x 480@60Hz/70Hz/72Hz/75Hz (VGA), 720 x 400@50Hz/60Hz/70Hz,
		720x576@50Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz (SVGA),
		832 x 624@75Hz, 1,024 x 768@60Hz/70Hz/75Hz (XGA),
		1,152 x 864@60Hz/75Hz, 1,280 x 720@60Hz, 1,280 x 800@60Hz,
		1,280 x 1,024@60Hz/75Hz (SXGA), 1,360 x 768@60Hz,
		1,440 x 900@60Hz/75Hz, 1,600 x 900@60Hz, 1,680 x 1,050@60Hz,
DP	Connector	DP 1EA
	Available Format	640 x 480@60Hz/70Hz/72Hz/75Hz (VGA), 720 x 400@50Hz/60Hz/70Hz,
		720x576@50Hz, 800 x 600@56Hz/60Hz/72Hz/75Hz (SVGA),
		832 x 624@75Hz, 1,024 x 768@60Hz/70Hz/75Hz (XGA),
		1,152 x 864@60Hz/75Hz, 1,280 x 720@60Hz, 1,280 x 800@60Hz,
		1,280 x 1,024@60Hz/75Hz (SXGA), 1,360 x 768@60Hz,
		1,440 x 900@60Hz/75Hz, 1,600 x 900@60Hz, 1,680 x 1,050@60Hz,
Audio	Connector	Audio Out
	Output Signal	Loop-through line level(PC only), Speakers : 2x10W
Application Support		Remote Controller
On Screen Display (OSD)		
Functions		VESA™ DPM Compatible
Language		Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified,Traditional), Japanese, Arabic
General		
Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<80W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions without Stand	967.0*560.0*73.5mm
	Bezel Size	8.6/16.4mm(Top/Bottom)
	Weight without Stand	7.6Kg
	Cabinet Color	Black
	VESA Mounts Interface	100*100mm /400*200mm
Accessory		Power cable, HDMI Cable, Remote Controller