SP01-001 Dome Mount

Product Features

- International Hole Pattern
- For Use With Spectra[®], DF5, and DF8 Series Pendant Domes (and Any Domes That Use 1.5-inch NTP Pipe)
- · For Outdoor and Indoor Use
- · Aluminum Construction, Gray Polyester Powder Coat
- · Cable Feedthrough
- Supports Up To 40 Pounds (18 Kg)
- · Easy To Install With Standard Tools

Description

The **SP01-001** dome mount is designed for outside and inside use with Spectra®, DF5, and DF8 domes, plus any other pendant dome that uses 1.5-inch (3.81 cm) NPT pipe. The mount attaches to rooftops and any flat horizontal surface. The flange was designed specifically for pole-top applications that use the 4.0-inch (10.16 cm) PCD (pitch circle diameter) mounting pattern commonly used in international applications. The **SP01-001** flange also has a 4.75-inch (12.0 cm) hole pattern that accommodates standard Pelco pedestal mounts. The **SP01-001** allows cable to be fed through the center of the tube to conceal wiring.

SP DISCLAIMER

SP products carry a 90-day warranty and are not returnable. SP products do not carry any agency certifications. Pelco strongly encourages installers to strictly follow local codes and regulations governing the installation of video security equipment and therefore assumes no liability for the installation of products depicted herein.

TECHNICAL SPECIFICATIONS

Construction Aluminum

Finish Light gray polyester powder coat

Suggested

Mounting Method Four 5/16-inch (7.94 mm) diameter


fasteners (not included) are


recommended 40 lb (18 kg)

Maximum Load 40 lb (18 kg)
Weight 3.25 lb (1.47 kg)
Shipping Weight 9 lb (4 kg)

(Design and product specifications subject to change without notice.)







NOTE: VALUES IN PARENTHESES ARE CENTIMETERS; ALL OTHERS ARE INCHES.