

PSI Displays Ltd



Suite C2, Butts Business Centre, Butts Road, Chiseldon, Swindon, Wiltshire, SN4 0PP. UK.



Tel: +44 (0) 1793 740456

e-mail: sales@psidisplays.co.uk Website www.psidisplays.co.uk

LCD COLOUR MONITOR Model: L215AT

21.5" TFT LCD Full HD, Wide Screen Colour Monitor, LED Back Light, AHD/TVI In/Out, HDMI, DVI, VGA, Audio In and Out via Speaker, I/R Remote Control.

Options: Touch Screen, Glass Front. Other sizes available.



Main Features:

- Resolution: 1920 x 1080P – Full HD
- Picture Ratio: 16:9
- Brightness: 250 cd/m2 - LED Back light.
- Contrast Ratio: 1000:1
- Inputs: AHD/TVI, HDMI, DVI, VGA, Audio.
- Outputs: AHD/TVI, Earphone.
- Mounting: VESA 75 or 100, Key Hole, Stand.
- 3D De-Interlaced Technology & Comb Filter.
- Anti-blur/image auto. • Fast Response time.
- Slim Aluminium cabinet in Black.
- Speaker 2 Watts max.

The L215AT with Full HD TFT technology offers Professional sharp images coupled with a high contrast ratio gives superb pictures. AHD/TVI In/Out, HDMI, DVI, VGA makes this is a truly versatile Monitor. Also boasting various mounting options and finished in a Smart tough Aluminium Metal housing. This compact unit is ideal for Multimedia Video and Surveillance system applications.

SPECIFICATIONS:

- Active area: 476.6 x 268.1 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 1.3/1.7 ms (Tr/Tf). • Viewing angle: Left/Right: 89°, Up/ Down 89°.
- Controls/Indicators: Front: On LED, I/R sensor, Source, Menu, Item, Up, Down, Power.
- Power Source: 12V DC, 1.92 Amp, 23 Watts approx. AC Adaptor: 100-240 Vac 50/60Hz 1.5Amp.
- Dimensions: 531.24 x 322.52 x 56.7 (71.2 with stand). Carton: 620 x 500 x 180 (WxHxD)mm.
- Weight: Unit: 4.66 Kgms, Carton: 6.79 Kgms. • Temp: Operation: 0°C~40°C, Storage: -20~ 60°.

Connections: AHD/TVI In/Out: BNC sockets. Full HD: HDMI Socket. DVI: DVI-D Socket. VGA:15 pin Sub-D. Audio L & R In: Phono sockets. Earphone: 3.5mm jack socket. DC input: 2.1mm socket. AC adaptor: IEC socket.

Standard accessories: AC adapter, AC Mains Lead, I/R Remote Control.

- All information is correct at time of going to press. Design and specification are subject to change without prior notice. E&EO