

4000 Series Audio Modules

4000 Series “4+1” & “5+1” Audio Speaker Modules



**AUDIO
MODULE**



**STANDARD
4+1 AUDIO**



**SENTRY
5+1 AUDIO**



Art. 4838-0



Art. 4838-1



Art. 4838-2



Art. 4838-0/M



Art. 4838-1/M



Art. 4838-1D/M



Art. 4838-2/M



Art. 4838-2D/M

Art.		4838-0	4838-1	4838-1D	4838-2	4838-2D
DESCRIPTION		Modular 4000 series “4+1” & “5+1” audio speaker				
BUTTONS	BUILT-IN	0	1	2	2	4
	MAX.	multiple combinations with the use of additional button modules: 4842, 4843, 4844, 4845, 4842D, 4843D, 4844D and 4845D				
FRONT FASCIA OPTIONS		Mirror Stainless Steel, /M Matt 316 Marine Grade Stainless Steel				
NAME PLATE & BACK LIGHT		No	Yes: 1 (backlit blue)		Yes: 2 (backlit blue)	
CALL PROGRESS LED’S		Yes: 4x LED’s, Busy, Call, Speak and Door Open				
MODULE PROGRAMMING		SW1: Call tone selection; No. of Rings (“5+1” system only); Conversation Time; Door Open Time SW2: Reassurance Tone (ON/OFF); System Type (“4+1” or “5+1”); Automatic recall when handset lifted (“4+1” system only)				
MODULE SIZE		1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm				
ADJUSTMENT POTS		Yes: Microphone and Speaker				
NO. OF RELAYS		1 internal relay				
RELAY CONTACTS		Dry Contacts (C/NO/NC)				
RELAY VOLTAGE / AMPS		Dry Contact Voltage/Current Rating: 24Vac/dc 2A max.				
PTE INPUT		Yes: 1x PTE switched 0V input (push-to-make)				
WORKING VOLTAGE		+12Vdc (compatible PSU’s: 520M and 521B)				
POWER CONSUMPTION		Stand-by: 25mA / During Call: 150mA / During Conversation: 70mA				
WORKING TEMP.		-10° to +50°C				