

DC-D4811WRX

8MP Vandal-Resistant IR Dome Camera/ NDA compliant



- 8MP(3840x2160) resolution
- Two-way audio
- PoE (IEEE 802.3af Class 3)
- IR LED (Distance : 30 m / 98.4 ft)
- Supports ONVIF
- Fixed-focal lens (f=3.3mm)
- Alarm in / out
- Day and night (ICR)
- 3-axis mechanical design for installation

- micro SD/SDHC/SDXC
- IK10 / IP67 supports
- True wide dynamic range (WDR)
- Easy installation with DirectIP NVR

SPECIFICATIONS

Video	
Image Sensor	1/2.8
Max. Resolution	3840 x 2160
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f=3.3mm
Aperture	F2.0(3.3mm)
Iris Control	Fixed Iris
Angular Field of View	101.3° (H) 54.5°(V) 119.7°(D) (f=3.3mm)
Pan/Tilt/Rotate Range	Pan: -170° ~ 170°, Tilt: -5° ~ 67.5°, Rotate: -109° ~ 109°
Min. Illumination	COLOR : 0.2 lux @ F2.0 B/W : 0 lux (IR LED ON)
Dynamic Range	120dB(True WDR)
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)
Day and Night	IR cut filter with auto switch
IR Distance (LEDs)	30m / 98.4 ft (4ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode(Sharpness, Contrast, Colors, Brightness Control)
Backlight Compensation	On / Off
Privacy Masking	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone
Network	
Video Compression	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported
Bitrate Control	H.265 - CBR / VBR, H.264 - CBR / VBR
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	30fps : 3840 x 2160 15fps : 3840 x 2160(WDR)
Supports Resolution	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360
Multi-video Streaming	Quaruple Streaming
Network Protocols	DirectIP 2.0 Protocol, IPv4, IPv6, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, uPNP, SNMPv2
Security	SSL Encryption, Multi-user Authority, IEEE 802.1x IP Filtering, HTTPS
Remote Access Client	DirectIP NVR Connection, IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
ALARM AND EVENT	
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with image)
Pre-recorded Voice Alert - IDIS protoco	On / Off
Audio In/ Out	1 / 1
Alarm In / Out	1 / 1
Environmental	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-20°C ~ 55°C(-4°F ~ 131°F) *Starting up at above 0°C (32°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	PoE (IEEE 802.3af Class 3)
Power Consumption	PoE, (IEEE 802.3af Class 3), 9.0W
Approval	FCC, CE, KC
Mechanical	
Dimensions (Ø x H)	Ø120.6 x 92.9mm
Weight	0.48kg(1.06lb)



PRODUCT IMAGE



DIMENSIONS



ACCESSORIES (OPTIONAL)

JUNCTION BOX	MOUNT ADAPTER	WALL MOUNT	CEILING MOUNT
DA-JB4700	DA-MA4300	DA-WM2050	DA-CM2050
Pole Mount	Corner Mount		
DA-LM2000	DA-RM2000		

ACCESSORY CONFIGURATION BY INSTALLATION ENVIRONMENT

PRODUCT	INSTALLATION ENVIRONMENT	ACCESSORY CONFIGURATION	
DC-D4811WRX	WALL	 JUNCTION BOX	Model: DA-JB4700
		or	
		 MOUNT ADAPTER	Model: DA-MA4300
		 WALL MOUNT	Model: DA-WM2050
	CELLING	 JUNCTION BOX	Model: DA-JB4700
		or	
		 CEILING MOUNT	Model: DA-CM2050
		 MOUNT ADAPTER	Model: DA-MA4300
	POLE	 POLE MOUNT	Model: DA-LM2000
		 MOUNT ADAPTER	Model: DA-MA4300
		 WALL MOUNT	Model: DA-WM2050
		or	
		 JUNCTION BOX	Model: DA-JB4700
		 POLE MOUNT	Model: DA-LM2000
		 MOUNT ADAPTER	Model: DA-MA4300
		 CORNER MOUNT	Model: DA-RM2000
	CORNER	 WALL MOUNT	Model: DA-WM2050
		or	
		 JUNCTION BOX	Model: DA-JB4700
		 CORNER MOUNT	Model: DA-RM2000