


NDAA Compliant 1/2.8" PTZ 4MP IP Dome Camera

VIP-P4MPX25IRVRAUAL



KEY FEATURES

NDAA compliant - NOVATEK chipset

4MP PTZ 25x zoom

Low light sensitive

100m IR illumination

4.8 - 120mm, motorised lens

IK10 vandal resistant and IP67 ingress protection

H.264/H.265 triple streaming

ONVIF compliant ONVIF Profile S, G and T

Storage - microSD card up to 256GB

BNC analogue port (aid comissioning)

Alarm and audio I/O

Analytics including: cross line, intrusion, enter and leave area detection

Vista's VIP series of IP cameras are fully NDAA compliant, allowing you peace of mind in offering one, consistent range that satisfies requirements across both private business and public sector projects.

This VIP Series 25x PTZ dome camera is equipped with AI auto-tracking software as well as manual control functionality to provide great flexibility and control. It suits a wide range of applications requiring pan, tilt and zoom operation with the 25x optical zoom feature allowing you to zoom in and identify faces or objects.

Low light technology provides IR illumination up to 100m.

The camera offers a full 360° pan range, perfect for monitoring a wide-open area. It provides detailed 4MP image resolution in robust, IK10 vandal resistant housing as well as an IP67 rating against water and dust.

It can deliver up to 3 streams in multiple formats inc. H.264, allowing you to optimise the quality of the video based on application. The latest H.265 technology reduces the levels of bandwidth and storage required.

Other features include Edge storage via MicroSD card slot that can take up to 256gb data, PoE and an internal microphone.

Accompanying the VIP series of cameras is the VIP series of IP NVR recorders - also NDAA compliant.

To learn more about Vista's NDAA compliant video surveillance products please visit www.norbain.com/brands/vista

TEL +44 (0) 118 912 5000



* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.

TECHNICAL SPECIFICATION

| Model | VIP-P4MPX25IRVRAUAL |
|---------------------------------|--|
| CAMERA | |
| Image Sensor | 1/2.8" 4MP, CMOS |
| Min Illumination | Colour: 0.003 lux F1.5, AGC on |
| WDR | 120dB WDR |
| Shutter Time | 1/100000s-1s |
| Optical/Digital Zoom | 25x/16x |
| Day/Night Mode | Day/Night/Auto/manual IR Cut filter |
| Signal/Noise | >56dB |
| LENS | |
| Focal Length | 4.8 - 120mm motorised zoom |
| Field of View | H = 52.20° - 2.74° V = 30.81° - 1.54° |
| Focus Control | Auto |
| Aperture Control | F1.5 - F3.8 Auto |
| PTZ | |
| Pan Range Pan Speed | 360° endless; Pan Manual Speed: 0.1° - 200°/s Pan Preset Speed: 240°/s |
| Tilt Range Tilt Speed | -15° - 90° (Auto Reverse); Tilt Manual Speed: 0.1° - 120°/s Tilt Preset Speed: 200°/s |
| Number of Presets | 1024 |
| Preset Tours | 16 Tours, up to 64 presets in each |
| Pattern Tour | 16 Pattern Tours, up to 128 actions in each |
| IR ILLUMINATION | |
| IR Distance wavelength | Up to 100m 850nm |
| VIDEO | |
| Max. Image Resolution | 2688 × 1520 |
| Primary Stream | 4MP (2688 × 1520), Max 30fps |
| Secondary Stream | 2MP (1920 × 1080), Max 30fps; |
| Tertiary Stream | D1 (720 × 576), Max 30fps; |
| Video Compression | H.265, H.264, MJPEG |
| Privacy Masking ROI | 24 masks 8 ROI |
| INTERFACES | |
| Ethernet | 1 × RJ45 10M/100M |
| Alarm Audio I/O | 2/1 1/1 |
| Video Output | 1 × BNC |
| Serial Port | 1 × RS485 |
| NETWORK | |
| ONVIF | Profile S, G and T |
| Network Storage | NAS, ANR |
| Security | Strong Password, HTTPS, Digest Authentication for RTSP, HTTP, TLS 1.2, WSSE and ONVIF |
| Protocol | IPv4, IGMP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS |
| AUDIO - 2-WAY | |
| Built-in Mic | n/a |
| Audio Compression sample rate | G.711U, G.711A 8KHz/64Kbps |
| INTELLIGENT ANALYTICS | |
| Video Analysis | Line cross, Intrusion, Enter & Leave Area detection, Auto Tracking, People Flow |
| EVENT AND STORAGE | |
| Storage | MicroSD, up to 256GB |
| Event Trigger | Motion, Audio and Tamper Alarm |
| GENERAL | |
| Working Condition | -40°C - 70°C (-40°F - 158°F) Humidity: ≤95% RH (non-condensing) |
| Environment | IP67 IK10 |
| Power Supply | DC12V (±25%,3A), PoE+ (IEEE 802.3at), 21W |
| Surge Protection | 6KV |
| NET Dimensions Weight | Ø166 × 295mm (Ø6.5" × 11.6") 3.05kg |
| COMPLIANCE | |
| NDAA | Yes, Novatek chipset |

MODELS IN THIS RANGE

0910430 VIP-P4MPX25IRVRAUAL
x25 PTZ IP67/IK10 and IR

ASSOCIATED PRODUCTS

0916470 VIP-CM01
Corner mount for VIP-P 25x PTZ (requires 0916630)

0916490 VIP-JB01
Junction box VIP-P 25x PTZ (requires 0916630)

0916590 VIP-PM02
Pole mount for VIP-P25x PTZ (requires 0916630)

0916630 VIP-WM01
Wallmount for VIP-P 25x PTZ

0785230 VPSU1241EXTe
12VDC 1 x 4A, IP68

OTHER PRODUCTS

0338110 VFS118WHDA 18.5"
Monitor TVI/AHD/CVBS/HDMI & VGA

0773530 VFS121WHDA 21"
Monitor TVI/AHD/CVBS/HDMI & VGA

0908420 VSW4
4 port PoE switch dual up link

0908430 VSW8
8 port PoE switch dual up link

0908440 VSW16
16 port PoE switch dual uplink

0908450 VSW24
24 port PoE switch dual uplink

0480540 CAT5e/UTP/305/PVC/GREY
305m Cat5e PVC cable drum - grey

0480560 CAT5e/UTP/305/LSZH/VIOLET
305m Cat5e LSZH cable drum - violet

0480580 CAT5e/UTP/305/DUCT/BLACK
305m Cat5e DUCT cable drum - black

0480610 CAT6/UTP/305/PVC/GREY
305m Cat6 PVC cable drum - grey

0480620 CAT6/UTP/305/LSZH/VIOLET
305m Cat6 LSZH cable drum - violet

0480630 CAT6/UTP/305/DUCT/BLACK
305m Cat6 DUCT cable drum - black

0853330 VCP-RJ45-Cat5-10
RJ45 Plugs × 10

0853350 VCP-RJ45-Cat6-10
RJ45 Plugs × 10

0853320 VSCT-RJ45
RJ45 crimp tool

0853380 VFCT-RJ45-Cat5-10
RJ45 FAST plug × 10

0853400 VFCT-RJ45-Cat6-10
RJ45 FAST plug × 10

0853370 VFCT-RJ45 FAST
RJ45 FAST crimp tool

0872170 DIAMOND4K
All in one CCTV\IP\Cable Test Monitor

