

PVM10CAMH

RETAIL APPLICATIONS MONITOR WITH 1080P
H.265 CAMERA



KEY FEATURES

1080p resolution

Highly detailed recorded images

H.265 video format

Greatly reduces the bandwidth and storage requirements to compatible recording solutions

Anti-mask alarm

Alerts staff if the device is being tampered with

Micro SD card slot

Records motion detection to a micro SD card if required

PoE powered

No need for additional mains spurs to be installed

IR remote

Easy set up

VESA mount

Multiple mounting options (rear VESA75 mount)

NDAA

Conforms to NDAA regulations



TEL
+44 (0) 118 912 5000

* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.



TECHNICAL SPECIFICATION

Model	PVM10CAMH
SCREEN	
Panel Type	10.1" LED
Resolution	1280 x 800
Viewable Size (mm)	216.96 x 135.6mm
Pixel Pitch (mm)	0.1695mm
Viewing Angle (H/V)	85/85/85/85
Contrast Ratio	800:1
Brightness	250 NIT
Response Time	30mS
IMAGE	
Resolution	1080p / 25ips
Sensor	1/2.8" SONY STARVIS CMOS Sensor
Lens	3.6mm fixed
Min Illumination	Colour: 0.1 Lux @F1.6 / BW: 0 Lux @F1.6
Noise reduction	2DNR, 3DNR
Dynamic Range	DWDR
Operation	TDN Auto
White balance	Auto, Incandescent, Fluorescent, Outdoor, Manual
Image effect	Flip, Mirror
Shutter speed	Auto, (1/10,000-1sec), Manual
VIDEO	
Compression	H.265/H.264 (Baseline, Main, High Profile), MJPEG
Bitrate	CBR, CVBR
Streaming	Dual Stream H.264 / H.265
SYSTEM	
Motion detection area	Up to 5 motion detection zones
Privacy	5 Programmable zones
Software reset	Restart, Reset, Factory Default
Remote Upgrade	Web browsing (IE, Chrome, Safari, Firefox), Smartmanager
SD Card recording	Event recording
EXTERNAL IN/OUT	
Alarm	1 input (NC / NO)
MicroSD	SDHC, SDXC (Max 256GB)
IR remote	Access to monitor OSD and basic camera functionality
Compatibility	ONVIF
ENVIRONMENTAL	
Operating temp	0°C to 40°C
Storage temp	-20°C to 60°C
Power source	12VDC or PoE (IEEE802.3af)
Power consumption	12W (Max)
Dimensions (WxHxD)	Net: 245 x 188 x 35mm Gross: 300 x 205 x 50mm
Weight	Net: 1.2Kg / Gross 1.4Kg
Mounting	VESA75x75
Casing	Metal
Colour	Black (front and case)
Certification	CE, RoHS

MODELS IN THIS RANGE

0912140 PVM10CAMH
10" Retail applications monitor with integral H.265 1080p camera

ASSOCIATED PRODUCTS

0857990 VESAPMX
Pole clamp bracket for 30-55mm pole diameter



0498620 VESAWM
VESA75/100 fixed wall mount



0498630 VESAWMPT
VESA75/100 pan/tilt wall mount



0498640 VESAWMPTPE
VESA75/100 pan/tilt wall mount with 250mm arm



0911920 LCD-IPMCA-b
Internal pendant mount ceiling adaptor



0911910 LCD-IPMGA-b
Internal pendant mount girder adaptor



0898200 VCBDEL2MB
2m pole, black



0911930 VESAPA1-b
VESA75/100 single monitor adaptor



OR
0264990 VESAPA2
VESA75/100 dual monitor adaptor



No liability will be accepted by Vista for any errors or omissions in this information | Subject to change without notice.

DS - PVM10CAMH - Version 1.1 2023-07-20



TEL
+44 (0) 118 912 5000

