

DS-D5019QE-B 19" LED Monitor


key Features

- LED backlit technology with HD 1366×768
- Wide view angle: 90°(H)/65°(V)
- 3D comb filter
- 3D De-interlace
- 3D noise reduction
- Input: HDMI, VGA
- VESA stand bracket

Model:

DS-D5019QE-B

Button Description



NO.	Description
1	Source button, show all signal input channel
2	Upward button, move cursor up
3	Downward button, move cursor down
4	Menu button, as a confirm button when setting parameters in the menu
5	Power on/off



DS-D5019QE-B

19" LED Monitor



Model	DS-D5019QE-B
Display	
Display Type	LED-Backlit TFT LCD
Screen Size	18.5"
Pixel Pitch(H×V)	0.300mm×0.300mm
Max Resolution	1366 × 768
Brightness	200cd/m ² (Typical)
Contrast	600:1
Response Time	5ms
Color	16.7M
Viewing Angle	Horizontal 90°, Vertical 65°
Input	
HDMI	HDMI × 1
VGA	VGA × 1
Mounting	
VESA	75mm x 75mm
General	
Power Supply	AC100 ~ 240V, 50 /60Hz
Consumption	< 20W(on) < 0.5W(Standby)
Operation Temperature	0°C ~ 40 °C
Operating Humidity	10%~85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5%~95% (No Condensation)
Dimension (W×H×D)	444.89mm×274.99mm×32.96mm (17.52" × 10.83" × 1.30")
Weight	4.0Kg(Gross weight) , 2.8(Net weight)