

# PRODUCT DATA

## **uPASS Reach AVI Long Distance Reader**

### **Product Description**

The uPASS Reach reader offers long-range vehicle identification up to 5 metres using the latest UHF technology. Based on battery-free passive UHF, the uPASS Reach reader offers a cost effective and enduring solution for parking access.

The system is based on a uPASS Reach reader and windscreenmounted UHF tags. The reader is installed next to the gate or barrier that is being controlled at a maximum height of 2 metres. A long-range passive UHF tag visible in direct line of sight will be identified up to 5 metres. The UHF tags are battery and maintenance free.

The reader output allows the access control system to open the gate/barrier when an authorised vehicle arrives without the need for the driver to present a card or badge. The built-in high intensity LED provides the user visual feedback that the tag has been read.



#### **Features**

- Consistent reading up to 5m
- On-site adjustable reading
- Elegant slim design
- LED and audible read indication
- Weatherproof housing
- Operates with passive UHF tags (EPC GEN 2)
- Self-adhesive windscreen tags
- Hand-held tags with dual-technology options

### **Specifications**

#### **Electrical**

Supply Voltage: 12 to 24V DC +10% (linear supply recommended)

Current cons: 1A @ 12V DC, 0.5A @ 24V DC

#### **Physical**

Dimensions: 200 x 220 x 45 mm (W x H x D)

Weight: 0.75 kg

Housing: Aluminium chassis with UL94 ABS cover

Protection: IP65

Operating temp: -30°C to +60°C

Mounting: Wall mounting as default. Pole mounting and adjustable

mounting kits available

#### Inputs/Outputs

Input: 1 dry contact or TTL

Relay output: 1 relay output (NO, common, NC), 24V DC, 2A

Output: Wiegand or Clock & Data (depending upon programmed tag

format)

Cable length: Wiegand 150m. 22AWG


**Operational** 

Operating freq: 865 - 868 MHz (902-928 MHz option available)
Detection range: Up to 5 metres with passive uPASS UHF tags



# **uPASS Reach AVI Long Distance Reader**

### **Application**



## **Ordering Information**

9942319	Long range AVI reader with identification at up to 5 metres. ISO 18000 EPC Gen2 compliant.	9215255	Long Range UHF Exterior Tag. Suitable for mounting on headlights.
9875840	uPASS Reach mounting set with adjustable arm.	9943943	Long range UHF tag in ISO card format, not suitable
7591152	uPASS Reach weather protection hood.		for windshield mounting. Programmed with secured customer specific ID number.
9945946	Long range UHF tag for windshield mounting. Programmed with secured customer specific ID number.	9942343	UHF - Mifare 1K Card. Credit card sized ISO credential with combined UHF and HF Mifare 1K technologies.
9946918	Tamper proof Long range UHF tag for windshield mounting. Destructs upon removal.	9943960	UHF - Legic Advant Card. Credit card sized ISO credential with combined UHF and HF Legic technologies.
9219641	UHF Vehicle identification tag designed for mounting on the exterior of the vehicle. Offers high performance on metal surfaces .	9942360	UHF – EM4102 Card. Credit card sized ISO credential with combined UHF and LF EM4102 technologies.







7591152



t: +44 (0) 1633 485533 f: +44 (0) 1633 485666

e: info@nortechcontrol.com

Nortech Control Systems Ltd. Nortech House, William Brown Close, Llantarnam Park, Cwmbran, NP44 3AB, United Kingdom

