AMG2035 **90 DEGREE DIN RAIL** WALL MOUNT BRACKET



Industrial Mounting Brackets

The AMG2035 is a single or dual DIN rail mounting bracket that allows for the 90 degree mounting of any AMG or 3rd party DIN rail devices in depth restricted installations.





[AMG2035*]



OVERVIEW

The AMG2035 DIN rail bracket supports all models from the AMG range that have a DIN rail mounting option as well as 3rd party DIN rail mountable equipment.

The mounting bracket is designed to offer 90 degree mounting of one or two devices within the equipment cabinet offering a simple and elegant mounting solution for depth restricted installations.

Supplied as a single DIN rail mount for one device and with an additional extension DIN rail for situations where two devices need to be mounted side by side or a single device with its appropriate DIN rail industrial power supply.

The design ensures that any units mounted maintain the necessary air flow space around them to ensure optimum operation even in harsh temperature environments.

The mounting bracket supports any DIN rail mountable power supply including all models from the AMG industrial power supply range which are available from 24-480W and with outputs of 12, 24 & 48VDC.

PSU and individual units must be purchased separately.

FEATURES

- Supports single or dual units mounted at 90 degrees to the wall surface
- Supports all AMG industrial DIN rail power supplies from 24 to 480W
- Unique AMG DIN rail design ensures that equipment cannot accidentally slide off the rails ensuring a robust mounting system
- Compatible with any AMG DIN rail mountable product
- Included extension piece transforms the bracket from a single unit to a dual unit mounting solution
- Supports 3rd party DIN rail mountable equipment
- Manufactured in the United Kingdom
- AMG Lifetime Support Warranty

* Power supply & individual units not included

AMG Systems Ltd. 3 The Omega Centre, Stratton Business Park, Biggleswade, Bedfordshire, SG18 8QB, UK :: +44 (0) 1767 600 777 E :: sales@amgsystems.com D39283-00 amgsystems.com



Environmental.

Operating Temp. -40 to +85°C / -40 to +185°F Storage Temp. -40 to +85°C / -40 to +185°F

Packaging.

Shipping Weight Dimensions

0.28kg / 0.62lb $(W \times D \times H)$ 160 × 80 × 80 mm 6.30 × 3.15 × 3.15 in

Mechanical.

Bracket	Anodised Aluminium
DIN Rails	Zinc Plated Steel
Dimensions	(W x D x H)
Single DIN Rail Version	75 × 75 × 75 mm
	2.95 × 2.95 × 2.95 in
Dual DIN Rail Extended Version	78 × 148 × 75 mm
	3.07 × 5.83 × 2.95 in
Installation	Wall / Surface Mount
DIN Rail Length	60 mm (2x 60mm lengths included)
	2.36 in
Weight	
Single DIN Rail Version	0.11kg / 0.24lb
Dual DIN Rail Extended Version	0.24kg / 0.53lb

Part Numbers.

AMG2035

90 Degree DIN Rail Wall Mounting Bracket With Extension, Industrial Grade

Recommended PSUs.

Non-PoE Power Supplies

AMGPSU-I12-P24 AMGPSU-I12-P54 AMGPSU-I24-P36 AMGPSU-I24-P60 DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 12VDC, 24W DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 12VDC, 54W DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 24VDC, 36W DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 24VDC, 60W

PoE Power Supplies AMGPSU-I48-P60 AMGPSU-I48-P120

AMGPSU-I48-P240 AMGPSU-I48-P480

DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 48VDC, 60W DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 47-53VDC, 120W DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 48-53VDC, 240W DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 48-55VDC, 480W

Notes.

NB:

PSU and individual units must be purchased separately



In a continuing effort to improve and advance technology, product specifications are subject to change without notice. Please visit www.amgsystems.com for the latest product specifications

AMG Systems Ltd. 3 The Omega Centre, Stratton Business Park, Biggleswade, Bedfordshire, SG18 8QB, UK :: +44 (0) 1767 600 777 E :: sales@amgsystems.com D39283-00 amgsystems.com

