

# Husky IVO 700R

Full redundancy for continuous recording



## Throughput

Up to 720 Mbit/s

## Local storage

Up to 64 TB

The Husky IVO 700 Rack is the ideal medium-sized video surveillance appliance that brings ease-of-use and full redundancy together – making it the perfect choice for those with a critical need for maximum uptime on their video installation.

### Redundancy for your peace of mind

No need to worry about losing video or OS failures – the Husky IVO 700R has it all covered.

- Full hardware redundancy with dual OS drives, power supplies and RAID
- Extensive configuration options on RAID
- Single point of contact for the support of both the VMS and the appliances
- Possibility for onsite support for hardware repairs and replacement

### Achieve more

It's always crucial to get the most out of your video solution – and to be able to achieve more with the same resources. The Husky IVO 700R removes the hassle of installation, compatibility and support – enabling you to save time and focus on more important aspects of your project.

- Seamless installation with Husky Assistant
- Remote management through iDRAC
- Extended camera compatibility – connect more than 11,000 devices to your XProtect® VMS

### Key features


- Rack-mount unit 1U form factor – ideal for those with an existing IT infrastructure
- Up to 64TB local storage
- Dual OS drives & power supplies
- Hardware RAID for increased redundancy
- iDRAC9 Enterprise

### Recommended usage

- Up to 100 channels (Based on the following video stream: 1080p, 30 FPS, 5-8 Mbit/s/channel, with video motion detection recording)
- XProtect management and recording server – viewing recommended on a separate

machine through XProtect Smart Client

- Remote viewing possible on Mobile or Web Client for up to 8 video streams, without affecting the overall performance



## Hardware information

### Form Factor

Rack Mounted 1U

### CPU

Intel® Xeon® E-2336

### GPU

No

### RAM

16GB DDR4

### Operating system (OS)

Windows 10 IoT Enterprise SAC

### VMS/OS Storage

2 x 240GB (RAID 1), M.2 SSDs

### Number of hard-drives

4 x 3.5" (hot-plug)

### Raw storage (gross)

16/32/48/64 TB  
(Dell Enterprise Grade 24/7 Drives)

### RAID Support

RAID Controller & Support  
PERC H755 SAS Front with Cache & Battery & Flash backup  
RAID 0,1,5,6,10  
RAID 5,6,10 configurable in Husky Assistant

### Display ports

1 x VGA

### Network interface

2 x 1 GbE (RJ45)

### Available PCIe slots

1 x PCI Express® x16 Gen 3 slot full height / half length card with x8 bandwidth

### Archiving to external NAS

Yes, through LAN port

### Credential and Key encryption

Trusted Platform Module (TPM) 2.0

### Redundant Power Supply

Yes, hot-plug

### Remote management

Yes, iDRAC9 Enterprise (license incl.)

## General information

### Hardware warranty

5 years full system warranty (incl. HDD)  
Onsite support next business day<sup>1</sup>

### Dimensions

42.8 x 434.0 x 534.5 (mm) (without Bezel)  
1.68" x 17.08" x 21.04" (without Bezel)

### Weight

13.6 kg  
29.98 lbs.

### Power input

100-240V, 50/60 Hz

### Max. power consumption

350W up to 94% efficient (Platinum) hot-plug redundant

### BTU Rating

924.3 BTU/h

### Protection

OVP (over voltage), OCP (over current), OTP (over temp), SCP (short circuit)

## Husky IVO 700R



## Environmental

This unit is intended for stationary server room and office use, according to the conditions stated below.

### Operating temperature

5° - 40° C / 41° - 104° F

### Storage temperature

-40° - 65° C / -40° - 149° F

### Humidity

10 - 85% relative humidity (non-condensing)

## Regulatory

### Safety & emission standards

CE (class A), UKCA, FCC, RCM, UL, Mexico (NOM), VCCI

### Trade compliance

NDAA Compliant

## Ordering information

<b>HE-700R-16TB</b>	Husky IVO 700 Rack mount, Win10, 16TB	4 bays x 4TB
<b>HE-700R-32TB</b>	Husky IVO 700 Rack mount, Win10, 32TB	4 bays x 8TB
<b>HE-700R-48TB</b>	Husky IVO 700 Rack mount, Win10, 48TB	4 bays x 12TB
<b>HE-700R-64TB</b>	Husky IVO 700 Rack mount, Win10, 64TB	4 bays x 16TB

### XProtect VMS software

Milestone Husky appliances are preloaded with Milestone XProtect VMS, which means that they can be used with any XProtect VMS variants. The required VMS licenses are purchased separately. The units can also be used with XProtect Essential+ with up to 8 cameras for free.

<sup>1</sup> Onsite intervention dispatched following Milestone's support processes - hardware Service Tag information accuracy required. Subject to regional availability, dependent on Dell Technologies support network. Dell Technologies onsite support service will be given on a best effort basis conditioned upon the location of the Husky IVO unit. Onsite support services like NBD or 4HR are being counted from the moment Dell Technologies' troubleshooting is finalized and conditioned upon the hour and the day of the week the troubleshooting finishes.