

Oneprox[™] GS3 LF Panel Reader

The PAC Oneprox[™] GS3 LF Panel Reader boasts simplicity and flexibility. Designed to fit many new or existing OEM door entry panels, the PAC Panel Reader can be seamlessly integrated into an access control system. With reliable reading of PAC's own LF Fobs, the Panel Reader is fully encapsulated and has been certified to IP65, making it ideal for external installations.

The Panel Reader also has a raised key symbol on the front and separate red and green LED's to offer both tactile and visual reassurance for the end user. In addition, the GS3 LF Panel Reader also provides multiple output formats such as Wiegand 26, enabling connection to many third-party access control platforms.

The Oneprox[™] GS3 LF Panel Reader is a versatile solution designed to fit many OEM Door Entry Panels in both new and existing external applications.

The Oneprox[™] GS3 LF Panel Reader's features and benefits:

- Robust Housing designed to fit into many OEM door entry panels
- Multiple outputs PAC, PAC64, Wiegand 26, Wiegand 34 and Wiegand Emulation mode to support many popular Wiegand formats
- Versatile simple on-site configuration via the built-in switches to define supported card formats and both variable and fixed output formats. No need for programming cards or specific readers
- Audiovisual identification two LED's (red/green) and audible sounder indicates valid/invalid card read
- Practical design high visibility LED's, enhanced sounder and tactile key symbol for the hard of hearing and visually impaired
- **Confidence** -lifetime guarantee against electronic failure



Contact our dedicated customer services team on:

+44 (0) 161 406 3400

to find out how you can start benefiting from a tailored PAC security system that accommodates your business' requirements.

"With quick and easy installation and the option of different outputs without the need for programming cards or specific readers, the PAC Panel reader allows us to carry a single product for multiple applications, saving both our time and the customer money."

> Part numbers: 909020117 -PAC Oneprox[™] GS3 LF Panel Reader (Black & Yellow) 909022117 -PAC Oneprox[™] GS3 Panel Reader (Blue & Grey)

Customer Support:

+44 (0) 161 406 3400 customerservices@stanleysecurityproducts.com PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ www.stanleysecurityproducts.com



Oneprox[™] LF Panel Reader specifications

Part Number	909020117 - PAC Oneprox [™] GS3 LF Panel Readers (Black & Yellow) 909022117 - PAC Oneprox [™] GS3 LF Panel Readers (Blue & Grey)
Dimensions	
Weight	90g
PAC Credentials	21020 - PAC Token (with clip) 20204 - PAC Token (without clip) 21039 - PAC Card pk of 10 21087 - STANLEY Token 20250 - KeyPAC Token 21030 - KeyPAC Card
ID Technology	PAC, STANLEY, KeyPAC and Wiegand Prox
Programmable Output Formats	PAC, PAC64*, Wiegand & Magstripe
Maximum Read Range	Up to 45mm
Intruder Grading	N/A
Environment	IP65 - Indoor/ Outdoor weather resistant
Operating Voltage	12V to 24V DC
Maximum Current Requirements @12V DC	<90mA @ 12V DC
Operating Temperature	-40° to +66°C / -40° to +151°F
Operating Humidity	10-85% RH @ 30±2°C / 85±4°F
Audio Visual Indication	Two LED's (red/green) and sounder
Tamper Output	N/A
Material	Polycarbonate
Certification	CE compliant under the R&TTE Directive
Recommended Cabling Type	6 core 24 AWG alarm cable unscreened for PAC or 5-conductor 22AWG for Wiegand
Boxed Product Contents	Reader and instruction manual

 * With PAC 512 or PAC 212 LF Controllers only

Ordering Information:

+44 (0) 161 406 3400 customerservices@stanleysecurityproducts.com PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ www.stanleysecurityproducts.com