

Relays

S342 Range

General purpose double pole relay module, supplied in various options, including individual, multiple, boxed or bulk packed, ideal for van stock.

Options Available

Individual

S342-1	12vdc powered	PCB only
S342-1/24	42vdc powered	PCB only

Dual

S342-2	12vdc powered	PCB Only
S342-2/24	24vdc powered	PCB only
S342-2B	12vdc powered	Boxed
S342-2B/24	24vdc powered	Boxed

Triple

S342-3	12vdc powered	PCB Only
S342-3/24	24vdc powered	PCB only
S342-3B	12vdc powered	Boxed
S342-3B/24	24vdc powered	Boxed

Quad

S342-4	12vdc powered	PCB Only
S342-4/24	24vdc powered	PCB only
S342-4B	12vdc powered	Boxed
S342-4B/24	24vdc powered	Boxed

20 Pack

S342-20	12vdc powered	PCB Only
S342-20/24	24vdc powered	PCB only

Specification

Led Current	N/A
Switch Contacts	DPCO contacts rated at 2A
Visual Indication	N/A
Integral Sounder Level	N/A
Supply Voltage	12vdc or 24vdc depending on version
Supply Input Current	60mA max per relay
Tamper	N/A
Material	PCB Module
Dimensions	40 x 34 x 14 mm per relay
Weight	0.038kg per relay
IP Rating	N/A
Approvals	UKCA and CE marked, ROHS compliant

Benefits and Features

- Two holes provided for permanent fixing
- Diode protection for polarity and coil back emf
- Screw terminals for easy connection
- Manufactured in the UK

