

Exitguard

EX125iS-H

Exitguard EX125iS-H is the steel cased version of the EX125i local door alarm designed specifically for integration with Grade 2 EN50131 intruder alarm systems, it is the ideal solution for all types of door security issues. This Exitguard is suited to harsh environments particularly where physical damage may occur. Any alarm or fault is communicated to the main intruder alarm system using a fully supervised loop circuit.

An **Auto Alarm Reduction** feature is incorporated to attenuate the sounder after a preset period to reduce the annoyance caused if the key holder is not immediately available. However, the sounder will restart if the door is opened again.

The **Safe Set** feature minimises false alarms caused by turning the EXITGUARD on without first closing the protected door.

The **Bleep In Off (BIO)** function can be enabled to provide a local audible and visual indication when the Exitguard is turned off. This reduces the likelihood of the Exitguard being left turned off.

The **unique design** virtually eliminates accidental damage of the unit in harsh environments. The wedge shape deflects any side impacts from passing objects, while the location of the keyswitch ensures that any potential damage to keys or the key barrel is minimised. The powder coated steel enclosure will fit discreetly into any installation, occupying minimal wall space. Selectable resistors on the alarm circuits allow for compatibility with key intruder panel manufacturers' systems. Selectable resistor options are (1k + 1k) or (2k2 + 4k7).

Specification	EX125iS-H
Audible Alarm Indication	Yes
Selectable Tones	Yes
Visual Alarm Indication	Yes
Audible/Visual off Indication	Yes
Sounder Output @ 1 m	108dB
Supervised Loop Output	Yes
Supervised Loop Alarm Output	Yes
Keyswitch Control	Yes
Unit Tamper	Yes
Compatibility	All Key Intruder Panels
Dimensions	171 x 71 x 51 mm
Replacement Key Barrels	Yes
Country of Manufacture	United Kingdom
Approvals	UKCA, CE marked, ROHS compliant

Benefits and Features

- Designed for grade 2 intruder systems
- High Power Piezo Sounder 108dB @1m
- Selectable Alarm Tones
- Visual Alarm Indication
- Keyswitch Control with random key numbers
- Audible / visual warning when turned off (BIO)
- FSL On / off monitor output
- Safe Set
- Tamper Switch
- FSL Alarm Output
- Selectable resistor values for outputs
- Simple Function Change by Internal Jumpers
- Compatible with key panel manufacturers

All Exitguards are supplied with fixings, door contact, 1 metre of cable and a door warning sign.

Typically cages are used in supermarkets to move goods from storage areas to the shelf. The EX125iS-H is designed in a steel enclosure with chamfered edges that deflect the cage as it passes by. The keyswitch is situated at the top to prevent any damages to the key or keyswitch.

