



Superior product line

Button S Jeweller

Wireless smart button.



2
GRADE
EN 50131

INCERT

SSF

IN PROGRESS

NFA2P

IN PROGRESS

What’s new

| | |
|---|---|
| Baseline Button Jeweller | Superior Button S Jeweller |
| Battery status is updated after each button press | Battery status is updated automatically once a day |
| Available for all PROs | Available only for accredited partners |

This is the device of the **Superior product line**. Superior products are advanced versions of the Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.

Operation modes

Button supports 3 modes: **panic button, automation device control, mute interconnected fire alarm**. Operation mode is adjusted by the PRO or user with admin rights in Ajax apps.

Event types


Button supports 8 event types: **intrusion, fire, auxiliary alarm, panic button, gas alarm, malfunction, leakage, custom**. Event type is adjusted by the PRO or user with admin rights in Ajax apps.

Protection against accidental alarm activation: double or long press




Jeweller communication technology

- Up to 1,300 m of radio communication in an open space
- Encryption and device authentication to prevent spoofing
- Regular polling to display current device statuses



Flawless autonomy

- Up to 5 years of operation
- Pre-installed battery
- Low battery warning
- Battery status supervision



Quick installation and setup

- Pairing with a hub via QR code
- Remote control and configuration in the app
- It can be carried around on the wrist, on the neck, or on the key ring
- Fixing on a flat surface with a Holder bracket (sold separately)



Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

| | | | |
|---|---|---|--|
| Compliance with standards EN 50131-3 (Grade 2) INCERT SSF (coming soon) NFA2P (coming soon) | Compatibility Hubs Hub Plus, Hub 2 (2G), Hub 2 (4G), Hub 2 Plus, Hub Hybrid (2G), Hub Hybrid (4G) Range extenders ReX, ReX 2 | Communication with control panel Jeweller communication technology Frequency bands 868.0–868.6 MHz Jeweller communication range up to 1,300 m In an open space. | Power supply Battery 1 × CR2032 Pre-installed. Battery life up to 5 years Manufacturer Renata |
| Installation Operating temperature range from –10°C to +40°C Operating humidity up to 75% Protection class IP55 | Enclosure Colour white, black Dimensions 47 × 35 × 13 mm Weight 16 g | Complete set Button S Jeweller 1 × CR2032 battery (pre-installed) Double sided tape Quick start guide | |



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/button-s/

- ✉ support@ajax.systems
- 📍 @AjaxSystemsSupport_Bot
- 🌐 ajax.systems