$\lambda J \lambda X$

Superior product line

StreetSiren S DoubleDeck Jeweller

Wireless outdoor siren with a clip lock for a branded faceplate.





What's new

IN PROGRESS

Baseline StreetSiren DoubleDeck Jeweller	Superior StreetSiren S DoubleDeck Jeweller
Jamming is detected only by the hub	Jamming is detected by both the hub and the siren
Common battery	Enhanced battery
Available for all PROs	Available only for accredited partners

This is the device of the Superior product line. Superior products are advanced versions of Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.



The main feature of **StreetSiren S DoubleDeck** is the Brandplate faceplate (sold separately). A security service provider can print their logo and contact information on the front panel of the siren.

The siren becomes an additional marketing channel to reach new customers like neighbours and visitors.







- Up to 1,500 m of radio communication in an open space
- Data is encrypted throughout the transmission process
- Regular polling to display current device statuses
- Alarms of the system's devices
- Security status: armed/disarmed
- Door opening (Chime function)
- After-alarm indication



- Tamper alarm
- Device authentication to prevent spoofing
- Jamming detection
- Holding screw to secure the device on SmartBracket

Flawless autonomy

- Up to 5 years of battery life
- Low battery notifications
- Panasonic pre-installed battery



- Pairing with a hub via QR code
- Remote control and configuration in the app
- Effortless installation and replacement

Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

Compliance with standards	Communication with control panel	Alerts	Features

EN 50131-4 (Grade 2) PD 6662:2017 IP54	Jeweller communication technology	Alarms Acoustic, LED	Types of notifications Acoustic, LED
INCERT (coming soon)	Frequency bands	Delay When Entering/Leaving	Alarm volume
SSF (coming soon)	868,0 — 868,6 MHz	Acoustic	from 85 to 113 dB
NFA2P (coming soon)			
	Communication range	Security mode change	Alarm duration
Compatibility	up to 1,500 m In an open space	Acoustic, LED	from 3 s to 3 min
Hubs		Security mode	Piezoelectric buzzer frequency
Hub Plus, Hub 2 (2G), Hub 2 (4G), Hub 2 Plus, Hub Hybrid (2G),		LED	3.5 ± 0.5 kHz
Hub Hybrid (4G)		Door opening (Chime function)	Clip lock for the Brandplate
		Acoustic	faceplate
Range extenders			(sold separately)
ReX, ReX 2		After-alarm indication LED	
Power supply	Installation	Enclosure	Complete set
Battery	Operating temperature range	Colour	StreetSiren S DoubleDeck Jeweller
4 × CR123A	from -25°C to +60°C	white, black	SmartBracket panel with holding screw
Battery life	Operating humidity	Dimensions	4 × CR123A batteries
up to 5 years	up to 95%	200 × 200 × 55 mm	(pre-installed)
			Installation kit
	Protection class	Weight	Quick start guide
	IP54	571 g	



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/streetsiren-s-doubledeck/



- @AjaxSystemsSupport_Bot
- ajax.systems