

# Biometric Access Control Made Simple

BioConnect makes it easy and cost effective to integrate biometrics into your access control system.

## Build an Advanced IP Access Control System with the Following Components

### ① INTEGRATION SOFTWARE



BioConnect ID Enterprise makes it easy and cost effective to integrate biometrics into your current access control system. With simple, secure and scalable features and functions, it is tailor-made for enterprises where verifying the true identity of people is critical for secure access to both physical facilities and software applications.

#### Features and Specifications:

- Advanced Template Management
- Access Control Release Level Certification
- Face/Finger Device Certification
- Scalable Architecture

### ③ ACCESS CONTROL SOFTWARE

BioConnect ID Enterprise is currently integrated with CCURE 9000 to provide seamless synchronization of all data.


**SOFTWARE HOUSE**  
*From Tyco Security Products*

### ② BIOMETRIC HARDWARE



BioConnect is integrated with Suprema biometric devices to provide assurance at all access points. Suprema is a global leader in biometrics and securities technology.

By combining world renowned biometric algorithms with superior engineering, Suprema is able to continually develop and manufacture reliable industry leading products including fingerprint and facial recognition access control.



## Support and Resources

BioConnect is dedicated to helping you successfully promote and sell Suprema and your Software House solution.

Phone:  
1-855-368-3743

©2017 BioConnect Inc. All rights reserved.

Web: [www.bioconnect.com](http://www.bioconnect.com)  
Sales: [sales@bioconnect.com](mailto:sales@bioconnect.com)  
Support: [www.bioconnect.com/support](http://www.bioconnect.com/support)



# Product Specifications



	FaceStation	BioStation 2	BioEntry W2	BioEntry Plus	BioLite Net	BioMini	
<b>Core Functions</b>	<b>Product Code</b>	FSM	BS2-OHPW (HID) BS2-OIPW (iClass SE) BS2-OIPW (EM) BS2-OMPW (Mifare)	BEW2-OAP (Multiclass) BEW2-OHP (HID) BEW2-ODP (EM)	BEPHOC(Prox) BEPLOC (Finger Only) BEPMOC (Mifare)	BC-BLNO	
	<b>Application</b>	Time & Attendance Access Control	Time & Attendance Access Control	Time & Attendance Access Control	Time & Attendance Access Control	Access Control	Enrollment
	<b>Authentication</b>	Face/Card/PIN	Finger/Card/PIN	Finger/Card	Finger/Card	Finger/Card/PIN	-
	<b>Card Options</b>	13.56 MHz Mifare	125 KHz EM 125KHz HID Prox 13.56 MHz Mifare	125 KHz EM 125KHz HID Prox 13.56 MHz Mifare 13.56 MHz iClass SE	125 MHz Prox 13.56 MHz Mifare 13.56 MHz iClass	13.56 MHz Mifare	-
<b>Capacity</b>	<b>Template Capacity</b>	10,000 (1:1) 1,000 (1:N)	1,000,000 (1:1) 40,000 (1:N)	1,000,000 (1:1) 200,000 (1:N)	10,000 (1:1)	10,000 (1:1)	-
	<b>Max. User</b>	10,000	500,000 (1:1) 20,000 (1:N)	500,000 (1:1) 100,000 (1:N)	5,000	5,000	-
	<b>Log Capacity</b>	1,000,000 (text) 10,000 (image)	3,000,000	1,000,000 (text)	50,000	50,000	-
<b>Interfaces</b>	<b>TCP/IP</b>	Yes	Yes	Yes	Yes	Yes	-
	<b>RS 485</b>	2 Channels	2 Channels	1 Channel	1 Channel	1 Channel	-
	<b>RS 232</b>	Yes	Yes	-	-	-	-
	<b>Weigand</b>	Yes	Yes	Yes	Yes	Yes	-
	<b>TTL I/O</b>	4 Inputs	2 Inputs	2 Inputs	2 Inputs	2 Inputs	-
	<b>Built In Relay</b>	2	1	1	1	1	-
<b>Other</b>	-	USB	-	-	-	-	
<b>Hardware</b>	<b>CPU</b>	6667MHz RISC x 1 1.1 GHz DSP x 1	1.0 GHz RISC	1.2 GHz Quad Core	533 MHz DSP	533 MHz DSP	-
	<b>Memory</b>	4GB Flash + 512MB RAM	8GB Flash + 128MB RAM	2GB Flash + 256MB RAM	8MB Flash + 16MB RAM	8MB Flash + 16MB RAM	-
	<b>LCD Display</b>	4.3" WVGA Touch Screen	2.8" Graphic LCD	-	-	128 x 64 Graphic LCD	-
	<b>LED Indicator</b>	Multi Color LED	Multi Color LED	Multi Color LED	Multi Color LED	Multi Color LED	-
	<b>IP Rating</b>	-	IP65 (Outdoor)	IP67, IK08	-	IP65 (Outdoor)	-
	<b>Tamper</b>	Switch	Supported	Supported	Switch	Switch	-
	<b>PoE</b>	Yes	Yes	Yes	-	-	-
	<b>Operating Voltage</b>	12V DC	12V DC	12V DC	12V DC	12V DC	-
	<b>Dimensions</b>	5.2 x 6.5 x 2.4	5.6 x 5.7 x 1.8	2 x 6.8 x 1.7	2 x 6.3 x 1.5	2.4 x 7.3 x 1.6	2.6 x 3.5 x 2.3

<b>BioConnect ID Enterprise</b>	Feature	CCURE 9000	Synchronized User Database	Max. Number of Devices	Recommended Users	Suprema Hardware	
	<b>Basic</b>	BC-BSC	Yes	Yes	20	> 50	Yes
	<b>Standard</b>	BC-STND	Yes	Yes	50	> 50	Yes
	<b>Pro</b>	BC-PRO	Yes	Yes	100	> 50	Yes

Additional Notes: Suprema biometric devices must be purchased from Software House to ensure BioConnect licensing compatibility.

Activate Software with Proof of Purchase at [www.bioconnect.com/activate](http://www.bioconnect.com/activate)

Web: [www.bioconnect.com](http://www.bioconnect.com)  
 Sales: [sales@bioconnect.com](mailto:sales@bioconnect.com)  
 Support: [www.bioconnect.com/support](http://www.bioconnect.com/support)

