



HPC3-NB-i3M2

High Performance Qube Client i3, 2 Monitor



SPECIFICATION

Intel 12th Gen i3	16GB DDR5	NVIDIA Quadro P400	3 x miniDisplayPort	1GbE LAN	1 x 250GB JBOD	None	Windows 10 Pro 64bit
RAID CONTROLLER	RAID BATTERY BACKUP	RAID CONFIG	REDUNDANT PSU	PSU	FORM FACTOR	IPMI REMOTE MANAGEMENT	ACCESSORIES
None	No	JBOD	No	High Efficiency 250W	Mini Qube	No	KB and mouse DVD Drive

TECHNICAL

Electrical	Physical	Environmental
100 - 240V, 50 - 60Hz CERTIFICATES: FCC, CUL, CE, EN6050/IEC-60950	DIMENSIONS: WIDTH: 211mm DEPTH: 280mm HEIGHT: 241mm WEIGHT:	OPERATING TEMP: 0C to 35C STORAGE TEMP: -40C to 60C HUMIDITY RANGE: 10% to 90% non-condensing

Reference *: SSD = Solid State Disk, HDD = Hard Disk Drive, GB = Gigabyte (1000 Megabytes), TB = Terabyte (1000 Gigabytes), R1 = RAID1, R5 = RAID5, R6 = RAID6, R50 = RAID50, R60 = RAID60, +HS = Hotspare, 1GbE = 1 Gigabit Ethernet, 10 GbE = 10 Gigabit Ethernet, SFP / SFP+ = Fibre network connection, CPU = Central Processing Unit, GPU = Graphics Processing Unit, OS = Operating System, IPMI = Remote out of band management, KB = Keyboard

