

GA-TEL-E1K4G



TELGUARD E1K 4G GSM - OPTIMUS

Optimus 4G GSM E1K. S/Steel Face Plate with Backlit Vandal Resistant Call Button & Backlit Vandal Resistant Keypad incl Trade & Clear. PSU & Aerial Included. Surface Mounted incl Low Profile Moulded Back Box and LED Down Light. PLEASE SPECIFY MONTHLY OR ANNUAL SIM OPTION

FEATURES

- 316 marine grade stainless steel faceplate
- 40mm low profile, high strength, anthracite grey allow cast back box
- LED downlight
- Stainless steel security screws
- Surface mounted
- Downward facing microphone
- THS Horwood quality sound
- Call up to 3 numbers from a single call point
- IP64 rated
- Time clock with 3 profiles
- 2 year warranty
- Backlit, vandal resistant keypad
- Timed trade button and clear button
- 100 pin codes for coded entry

Special price £435.00 + VAT

Offer ends 31/12/2023

**** Please call the office to order ****

TECHNICAL INFORMATION

- Power: 12 Volt 1 Amp. DC PSU fitted with a 3A fuse (supplied and must be dedicated to the Telguard intercom unit). Power consumption: 120 mA Idle @ 12 Volts
- Telephone type: Standard DTMF (Dual Tone Multi Frequency) generating telephone, cordless or mobile phone.
- Programming: Remotely programmable via App, SMS or via GSM modem. Locally via USB cable.
- Relays: 3: 1 x 2A, 2 x 200mA, 2 x Auxilliary Inputs
- Relay Activation Time: 1 - 60 seconds, adjustable locally and remotely.
- Operating Commands: # Pulses RL1, 1# Pulses RL1, 2# Pulses RL2, 3# Latches RL3, 6# Unlatches RL3
- Time Clocks: This utilizes the on board time clock enabling custom profile functions to be activated
- Authorised Call Access: 100 telephone numbers can be stored. Calling the unit, from an authorised telephone number activates the relay.
- Dimensions: H 224 x W 96 x D 40mm