

FP3

Manual Call Point

The FP3 is available in a variety of colours to suit different applications. The red is available as single pole and is certified to EN54-11 and CPR. The green, white and yellow are available as single or double pole.



Single Pole		Double Pole
<i>Resettable (Plastic) Non-resettable (Glass)</i>	Operating Element	<i>Resettable (Plastic) Non-resettable (Glass)</i>
<i>Single change over</i>	Switch Type	<i>Double Pole change over switch</i>
<i>12-24 Volts DC</i>	Operating Voltage	<i>12-24 Volts DC</i>
<i>15A 125/250V AC</i>	Contact Rating	<i>15A 125/250V AC</i>
<i>Red LED</i>	LED Indicator	<i>Red LED</i>
<i>2.5mm Insertion type rated 10A 250V</i>	Terminal Type	<i>2.5mm Insertion type rated 10A 250V</i>
<i>IP44. For internal use only</i>	IP Rating	<i>IP44. For internal use only</i>
<i>-10°C to +55°C</i>	Temperature Range	<i>-10°C to +55°C</i>
<i>Case ABS. Operating elements glass or polycarbonate</i>	Materials	<i>Case ABS. Operating elements glass or polycarbonate</i>



Contact us:

Phone:

Tel: +44(0)151 6061000
Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk
Email: info@cqr.co.uk



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

