


12VDC External IP68 Power Supplies

VPSU12xxEXTe



VPSU1221EXTe & VPSU1241EXTe



VPSU1244EXTe



VPSU1248EXTe

KEY FEATURES

12VDC output

IP68 External enclosure

Supplied with compression glands and mounting fixings

Supplied with additional fuses

TECHNICAL SPECIFICATION

MODEL	VPSU1221EXTe	VPSU1241EXTe	VPSU1244EXTe	VPSU1248EXTe
INPUT				
Voltage	90-264V ac			
Frequency	50-60Hz			
Fuse (F5)	T2A - 20mm 230V HRC			
Max input current	1.5A			
OUTPUT				
No. of outputs	1	1	4	8
Voltage	11.4 - 12.6V dc (12V dc nominal)			
Max load current	2A	4A	4A	4A
Ripple	150 mV pk-pk max			
Fuse	F2A - 20mm Glass type - 230V	F4A - 20mm Glass type - 230V	4 of 1APTC	8 of 500mA PTC
Overload	Electronic shutdown until overload or short circuit removed			
PHYSICAL				
Environment	-10°C to 40°C @ up to 95% RH, IP68 external enclosure			
Dimensions	200H x 150W x 100D (mm)			
Mounting holes	182.5 x 131 (mm)			
Weight	Approx 1.05Kg			
Compliance	Low Voltage: 2014/35EU, EMC: 2104/30/EU, RoHS2: 2011/65/EU, WEEE: 2012/19/EU			

MODELS IN THIS RANGE

0785220 VPSU1221EXTe

0785230 VPSU1241EXTe

0785240 VPSU2481EXTe

0785250 VPSU1248EXTe



No liability will be accepted by Vista for any errors or omissions in this information | Subject to change without notice.

VPSU12XXEXTe - Version 1 06/24



TEL
+44 (0) 118 912 5000



* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.