



# Public viewing monitors with 1080p camera, Non PoE

PVM32CAMLV & PVM43CAMLV



## KEY FEATURES

### 1080p resolution

Highly detailed recorded images

### H.265 video format

Greatly reduces the bandwidth and storage requirements to compatible recording solutions

### Anti-mask alarm

Alerts staff if the device is being tampered with

### Micro SD card slot

Records motion detection to a micro SD card if required

### IR remote

Easy set up

### VESA mount

Multiple mounting options

### NDAA

Conforms to NDAA regulations

### Non PoE powered

Requires power

The Vista Non PoE Public Viewing Monitors are available in 32" and 43" respectively, each is provided with a built-in 1080p H.265 IP camera. Each adds to Vista's existing PVM armoury to assist the retailer in their fight to reduce shrinkage and protect profits by covering larger retail areas such as aisles or wider store entry/exit points.

The retailer's logo can be displayed on-screen, then, when a customer approaches, the motion detection function will switch the display to a live view of the camera. If required it can also display a variety of messages, e.g. "Recording in progress", along with recording to a microSD card. If the camera is covered, the Anti-mask function is triggered and an audible alarm activated via the built in speakers.

For contrasting scenes of view, both have a DWDR function to provide balanced exposure, ensuring highly detailed images are seen, reducing and eliminating back-lighting issues. The combination of the 3.6mm wide angle lens and VESA mounts allow the PVMs to be easily mounted in landscape mode. The camera lens can then be positioned either above the display screen or below it. To protect any personal information within the scene of view (e.g. chip and pin machines), there are 8 user-definable privacy zones which can be applied locally at the screen and across all IP image streams for total security and peace of mind.

Both PVMs include the power cable/PSU for ease of installation. ONVIF compliance ensures they can be used on multiple manufacturers' recording platforms.



TEL  
+44 (0) 118 912 5000

\* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.



## TECHNICAL SPECIFICATION

Model	PVM32CAMLV	PVM43CAMLV
<b>SCREEN</b>		
Panel Type	32" LED	42.5" LED
Resolution	1920 x 1080	
Viewing Angle (H/V)	89/89/89/89	
Contrast Ratio	1200:1	
Luminance	400 cd/m2	
Response Time	8mS	
<b>IMAGE</b>		
Max Resolution	1080p / Up to 30ips	
Sensor	1/2.8" SONY CMOS Sensor	
S/N Ratio	50dB	
Lens	3.6mm fixed F2.6	
Min Illumination	Colour: 0.1 Lux @F2.6	
Noise reduction	3DNR	
Dynamic Range	DWDR	
White balance	Auto	
Image effect	Flip, Mirror	
Shutter speed	Auto	
<b>VIDEO</b>		
Compression	H.265/H.264	
Bitrate	CBR, VBR	
Streaming	Dual Stream H.264 / H.265	
<b>SYSTEM</b>		
Motion detection area	Up to 5 motion detection zones	
Privacy	5 Programmable zones	
Software reset	Restart, Reset, Factory Default	
Remote Upgrade	Web browsing (IE, Chrome, Safari, Firefox), Discovery Tool	
SD Card recording	Event recording / Continuous / Schedule	
<b>EXTERNAL IN/OUT</b>		
Ethernet	(10/100) RJ45 (non POE)	
Mic In	1 x external - 2-pin phoenix push open terminal	
Alarm	1 x input (NO/NC)   1 x output (NO/NC 20VDC @ 150mA)	
Edge Storage	MicroSDHC, MicroSDXC Up to 256GB	
IR remote	Access to monitor OSD and basic camera functionality	
Compatibility	ONVIF (Profile M, S, T)	
Audio	2W Speaker x2	3W Speaker x 2
<b>ENVIRONMENTAL</b>		
Operating temp	0°C to 40°C	
Storage temp	-20°C to 60°C	
Power IN	DC24V	AC100-240V
Adapter power IN	AC100-240V	N/A
Power consumption	<60W (Max)	<80W (Max)
Dimensions (WxHxD)	Net: 718 x 455 x 53mm Gross: 910 x 683 x 222mm	Net: 964 x 590 x 72mm Gross: 1105 x 755 x 200mm
Weight	Net: 8.84Kg / Gross: 12.0Kg	Net: <17Kg / Gross: <21Kg
Mounting	VESA 100 x 100, 200 x 100	VESA 200 x 200, 400 x 200
Colour	Black (front and case)	
Certification	CE, RoHS, LVD	

### CONTENTS LIST

- PVM Monitor
- IR Remote
- 24v PSU or mains lead included
- Scan Me Label

## MODELS IN THIS RANGE

**0936660 PVM32CAMLV**  
32" Non PoE PVM

**0946000 PVM43CAMLV**  
43" Non PoE PVM

## ASSOCIATED PRODUCTS

**0911920 LCD-IPMCA-b**  
TFT pole ceiling adapter black

**0911910 LCD-IPMGA-b**  
TFT Pole girder adapter black

**0092210 VCBDEL2M**  
38mm 2m pole, chrome

**0898200 VCBDEL2MB**  
38mm 2m pole, Black

### PVM32CAMLV only:

**0911940 VK2PVMPA1-B**  
Pole mount for 1 x VESA 200 x 100 (90° rotatable)

**0911930 VESAPA1-b**  
VESA 75 x 75 and 100 x 100 TFT pole adapter

### PVM43CAMLV only:

**0483910 VESAPA32e**  
Large single TFT pole adaptor 200 x 200

