

AXIS T94Q01A Wall Mount

Aluminum wall mount

When used together with AXIS TQ1601-E Conduit Back Box, the Ethernet cable can be routed through cable protection pipes/conduits along the wall (from left or right). AXIS T94Q01A is IK10 rated, and compatible with all Axis outdoor fixed box cameras and housings.

> [Aluminum](#)

> [IK10 rated](#)



AXIS T94Q01A Wall Mount

General		Approvals	Environment
Supported products	AXIS TQ1601-E Conduit Back Box AXIS T98A16-VE Surveillance Cabinet AXIS T91A47 Pole Mount AXIS T92E Series AXIS T93F Series AXIS P13-E AXIS Q16-E AXIS T92G20 Outdoor Housing		IEC/EN 60529 IP66/IP67, NEMA 250 Type 4X ^a Impact IEC/EN 62262 IK10
Maximum load	7 kg (15.4 lb)	Weight	650 g (1.4 lb)
Angle	Tilt: +25° to -65° Pan: +100° to -100°	Dimensions	206 x 75 x 131 mm (8.11 x 2.96 x 5.17 in)
Cable routing	Internal	Sustainability	PVC free
Environment	Indoor/outdoor	Included accessories	Installation Guide
Material	Powder coated, Chromate aluminum Color: white NCS S 1002-B Stainless steel screws (captive)	Required accessories	Torx 30 Bit
		Warranty	3-year warranty, see axis.com/warranty

a. *Corrosion protected only*

Environmental responsibility:
[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)