

AXIS T93C10 Outdoor Housing

Vandal-resistant with active cooling and heating

AXIS T93C10 Outdoor Housing is optimized for Axis network cameras using EF/EF-S-lenses. The housing is built to help maintain optimal conditions for sensitive components, operating between -40 °C and 70 °C (-40 °F and 158 °F). AXIS T93C10 protects against the ingress of dust and water, and features two sealed cable ports. The non-metallic housing is impact-resistant and will not corrode, rust, or oxidize. AXIS T93C10 can be installed on walls using the included heavy-duty wall mount or on poles with the optional pole mount.

- > [Active cooling and heating](#)
- > [Protection against impact, water, dust, UV and corrosion](#)
- > [Optimized for Axis network cameras using EF/EF-S lenses](#)
- > [Included wall mount](#)
- > [Optional pole mounting accessory](#)



AXIS T93C10 Outdoor Housing

Supported products	AXIS Q1659 100 mm, f/2.8	IEC/EN/UL 60950-1, IEC/EN/UL 60950-22
	AXIS Q1659 85 mm, f/1.2	Environment
	AXIS Q1659 55-250 mm, f/4-5.6 (With AXIS T93C Extension Kit)	IEC 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10
	AXIS Q1659 50 mm, f/1.4	With AXIS T93C Extension Kit: IEC 60529 IP66,
	AXIS Q1659 35 mm, f/2	NEMA 250 Type 4X, IEC/EN 62262 IK10
	AXIS Q1659 24 mm, f/2.8	
	AXIS Q1659 10-22 mm, f/3.5-4.5	
Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure	Weight
	With AXIS T93C Extension Kit: IP66- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure	With wall mount: 5.5 kg (12 lb)
	Color: White	Without wall mount: 3.7 kg (8.2 lb)
Power	Input voltage 24 V DC, max consumption 8.0 A 192 W	Dimensions
	Camera output voltage 24 V DC, max 1.25 A 30 W	Exterior, without wall mount (LxHxW): 530 x 140 x 190 mm (21 x 5.4 x 7.4 in)
Connectors	DC input terminal block	Interior (LxHxW): 300 x 95 x 130 mm (11.8 x 3.75 x 5.0 in)
Operating conditions	-40 °C to 70 °C (-40 °F to 158 °F)	Maximum EF-lens dimensions with AXIS Q1659: ø 112 x 120 mm (ø 44 x 47 in)
	With AXIS Q1659: -40 °C to 50 °C (-40 °F to 122 °F)	Sustainability
	Humidity 10-100% RH (condensing)	PVC free, BFR/CFR free
Approvals	EMC	Included accessories
	EN 55024, EN 55032 Class B, EN 50581, EN 50130-4,	Installation guide, heavy-duty wall mount, IP68 cable gaskets
	EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B,	Optional accessories
	ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B,	AXIS T93C Wall-and-Pole Conduit Backbox, Power Supply PS24
	KCC KN32 Class B, KN35	240 W, AXIS T93C Extension Kit
	Safety	Warranty
		3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility