

DH-2026PF

24 Port PoE switch



- Individual port data transmission to DirectIP™ NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Maximum per-device PoE delivery of 360W available for 1~24 RJ45 ports
- Central power control for greater network utility
- Supports 24 FE RJ45 ports and Uplink 2 GbE RJ45 / 2 GbE SFP combo slots

SPECIFICATIONS

System	
System Memory	32MB SDRAM, 16MB Flash
Switching Capacity	8.8Gbps
Connectivity	
Copper Service Port	24 RJ45Connectors (10/100BASET)
Optical Uplink Port	2 RJ45/ SFPcombo (10/100/1000BASET/1000BASEX)
PoE Power	
supported Standards	IEEE802.3af2003 / IEEE802.3at2009
PD Connection	Up to 24 IEEE802.3afPDs or Up to 12 IEEE802.3atPDs
PSE Power	360W
General	
Diemensions(W x H x D)	430mm x 44mm x 235mm (17.0" x 1.7" x 9.3")
Weight	2.62Kg (5.77lb)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Input	100-240V~, 50/60Hz, 5.0-2.5A, 450W
Power Consumption	450W
Approvals	FCQ CE KQ UL CB



PRODUCT IMAGE



DIMENSIONS

