

DR-2516P-A

DirectIP™ 2500 Series H.265 4K Recorder



- Total incoming throughput 320Mbps
- Supports UHD display
- Built-in 8 channel PoE Switch
- Up to 480ips UHD real-time recording
- Up to 480ips live display
- Supports one click network configuration through FEN service
- Supports H.265 / H.264 codec
- Easy to install, set-up and play with DirectIP™ cameras
- Supports third party cameras (Axis, Panasonic, ONVIF™)

SPECIFICATIONS

Video	
Video Inputs	16 IP channels
Max. Incoming Throughput	320Mbps
Supported Camera	DirectIP™, AXIS, PANASONIC, ONVIF™
Video Outputs	1 HDMI, 1 VGA
Display Resolution	HDMI : 3840x2160, 1920 x 1200 , 1920 x 1080, 1680 x 1050, 1600 x 1200 VGA : 1920 x 1200 , 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 480ips
Digital Zoom	x2 ~ x12
Recording	
Max. Throughput	180Mbps, 480ips@UHD
Recording Resolution	Up to 12MP (Depending on IP Camera)
Video Compression	H.265, H.264
Recording Mode	Time-Lapse Event, Pre-Event, Panic
Trigger Event	IDLA(Object Detection, Intrusion, Loitering, Line Crossing Face Detection), BI(Exceed Occupancy Limit, Social Distancing, Mask Rule Violation, Queue Congestion), Motion , Trip-zone, Tampering, Video Loss Audio Detection, Alarm In, Network Alarm, Text-in, System, Etc.
Playback	
Performance	16ch synchronous playback 8ch 4K playback
Search Mode	Time-lapse Event Log, Text-in, Thumbnail Metadata (via IDIS Center, IDIS Solution Suite)
Digital Zoom	x2 ~ x12
Storage	
HDD	SATA x 2, eSATA x 1
Network	
Client Connection	Gigabit Ethernet(Client) x1
Video In Connection	FastEthernet(IP Camera) x8 + Gigabit Ethernet (Ext) x1
Transmission Speed	50Mbps / 100Mbps(BRPMODE)
PSE Power	PoE(IEEE802.3at class4) supported 8 ports, 100W
Event Notification	Email(attach clip (.cbf) .MP4), Callback to Remote S/W, Push notification (IDIS Mobile)
Two-way Audio	Yes
Interface	
Audio In / Out	Local(NVR) : - / 1RCA+ 1HDMI IP Camera: 16 / 16 (Depending on IP Camera)
Alarm In / Out	Local(NVR) : 4 / 1 IP Camera: 16 / 16 (Depending on IP Camera)
Serial Interface	RS232(Terminal Block)
USB	USB2.0 x 1, USB3.0 x 1
User Interface	Mouse, IR Remote Control, Network Remote Keyboard
General	
Operating System	Embedded Linux
Environmental	
Operating Temperature	0°C to 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Consumption	NVR: 12V=, 2.2A 26.4W PSE 54V=, 1.85A 100W MAX
Approval	FC, CE, KC
Mechanical	
Unit Dimensions (W x H x D)	300mm x 62mm x 231mm (11.8" x 2.4" x 9.1")
Unit Weight	2.3kg (5.1lb) (with 1 HDD)



PRODUCT IMAGE



DIMENSIONS

