


# NDAA Compliant 32 Channel Non-PoE NVR with Dual NIC Cards

VIP-NVR3212MP-NP



Vista's VIP series of NVRs are fully NDAA compliant, allowing you peace of mind in offering one, consistent range that satisfies requirements across both private business and public sector projects.

The VIP-NVR3212MP-NP is a Non-PoE Network Video Recorder with Dual NIC Cards - for installs where you wish to separate the customer's video surveillance cameras from their network to facilitate Multi Addresses, Fault Tolerance or Load Balance. This 32-channel recorder is Vista's highest spec of NVR, allowing for a superior throughput of data and recording capacity, it supports cameras up to 12MP image resolution along with 4K monitors.

Multiple fisheye dewarping modes for live view and playback across both web interface and GUI. You also benefit from SMART video analytics.

Integral to the range is Vista's intuitive video management & remote software - Vizion. Vizion Remote allows you to control PTZ cameras, view live and recorded footage, manage devices and event push notifications, all remotely via your mobile phone. Vizion Desktop is a PC Based viewing client for Windows & Mac OS systems, easy to deploy video management software, with features such as live view, playback, device management, recording schedule, alarm configuration, video wall, people counting, and e-map.

The VIP-NVR3212MP-NP offers both audio and alarm input and output, evidence review and Raid capability.

## KEY FEATURES

### NDAA Compliant

Support H.265/H.264  
video formats

32 channel input

ONVIF Profile S, G and T

VGA and HDMI  
independent output

12MP IP camera support

Supports cloud upgrade

Non PoE

Dual NIC

To learn more about Vista's NDAA compliant video surveillance products please visit [www.norbain.com/brands/vista](http://www.norbain.com/brands/vista)



TEL  
+44 (0) 118 912 5000



## TECHNICAL SPECIFICATION

Model	VIP-NVR3212MP-NP
<b>DECODING</b>	
Decoding Format	H.265, H.264
Decoding Capability	H.265: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 6 x 5MP@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30, 32 x 960P@25 H.264: 2 x 16MP(4800*2688)@30, 2 x 12MP@30, 2 x 4K@30, 4 x 5MP@30, 6 x 4MP@30, 8 x 3MP@30, 14 x 1080P@30, 30 x 720P@30, 32 x D1
Audio Compression	G.711A, G.711U
<b>NETWORK</b>	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	160Mbps
Remote Users	128
Protocols	TCP/IP; P2P; UPnP; NTP; DHCP; PPPoE; HTTP; HTTPS; DNS; DDNS; SNMP; SMTP; RTSP; 802.1x; IPV6
Browser(Plugin)	Windows:IE (IE10/11), Firefox (version 52.0 and above), Chrome (version 45 and above), Edge (version 79 and above)
<b>VIDEO/AUDIO INPUT</b>	
IP Video Input	32 ch
RCA Audio Input	1 ch
<b>VIDEO/AUDIO OUTPUT</b>	
HDMI Output	HDMI:4K(3840x2160)/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA Output	VGA:1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
RCA Audio Output	1 ch
Liveview Display	1/4/6/8/9/16/25/32
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
<b>TWO-WAY AUDIO</b>	
Two-way Audio	1 ch, RCA (Using the audio input and output)
<b>SNAPSHOT</b>	
FTP/Schedule/Event Snapshot	4 ch snapshot, up to D1 resolution
<b>RECORDING</b>	
Recording Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF/CIF
Synchronous Playback in Local	16 ch
<b>SMART</b>	
VCA Detection by IPC	Face Detection; face detection; Vehicle Detection; SIP(Intrusion Detection, Cross Line Detection, Enter Area, Leave Area); Ultra Motion Detection(UMD); Temperature Detection(Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection); People Counting(People Flow Counting, Crowd Density Monitoring); Video Metadata; Traffic Monitoring
VCA Search	Motor Vehicle Search; Non Motor Vehicle Search; Human Body Search; General Search; People Counting Report; Heat Map
SMART by IPC	All channels (up to 8 images/s in total)Face Detection, face detection, Vehicle Detection, Temperature Detection, SIP, UMD, Video Metadata, Traffic Monitoring
<b>ALARM</b>	
General Alarm	Defocus Detection; Scene Change Detection; Object Left Behind; Object Removed; Auto Tracking; Motion Detection; Tampering; Human Body Detection; Video Loss; Alarm Input; Audio Detection
Alert Alarm	IP Conflict; Network Disconnected; Disk Offline; Disk Abnormal; Illegal Access; Hard Disk Space Low; Hard Disk Full; Recording/Snapshot Abnormal
<b>HARD DISK</b>	
SATA	4 SATA Interfaces
Capacity	Up to 16TB for each HDD (The maximum HDD capacity varies with environment temperature)
Disk Group	Support
Redundant Storage	Support
Disk Array Type	RAID 1, 5
<b>EXTERNAL INTERFACE</b>	
Network Interface	2 RJ45 10M/100M/1000M self adaptive Ethernet Interface
USB	Front: 1 x USB2.0; Rear panel: 1 x USB2.0, 1 x USB3.0
RS485	1
Alarm In	16 ch
Alarm Out	4 ch
Power Supply	DC 12V/5A
<b>WORKING ENVIRONMENT</b>	
Working Temperature	10 °C - 55 °C (14 °F - 131 °F)
Working Humidity	≤ 90% RH (non condensing)
Power Consumption (without HDD)	≤ 20W
<b>DIMENSIONS</b>	
Weight (without HDD)	≤ 3.4Kg (7.50lb)
Dimensions	440mm × 344mm × 48mm (17.3"×13.5"×1.9")

## MODELS IN THIS RANGE

**0952920 VIP-NVR3212MP-NP**  
32CH 12MP H.265 HD Non PoE NVR NDAA

**0910650 VIP-NVR1612MP**  
16CH 12MP H.265 HD PoE NVR NDAA

**0910660 VIP-NVR3212MP**  
32CH 12MP H.265 HD PoE NVR NDAA

**NOTE:** For HDD configurations speak to your account manager for pricing today

## OTHER PRODUCTS

**0913720 VistaPC-i5-G12-3Mon-KBM ClientPC**

Windows Client i5 PC with OTB storage, 3-monitor support

**0913730 VistaPC-i5-G12-3Mon-KBM-2TB Srv/Client**

Windows Client i5 PC with 2TB storage, 3-monitor support

**0338110 VFS18WHDA 18.5"**  
Monitor TV/AHD/CVBS/HDMI & VGA

**0773530 VFS121WHDA 21"**  
Monitor TV/AHD/CVBS/HDMI & VGA

**0908420 VSW4**  
4 port PoE switch dual up link

**0908430 VSW8**  
8 port PoE switch dual up link

**0908440 VSW16**  
16 port PoE switch dual uplink

**0908450 VSW24**  
24 port PoE switch dual uplink

**0946300 Diamond4kv2**  
All in one CCTV\IP\Cable Test Monitor



No liability will be accepted by Vista for any errors or omissions in this information. Subject to change without notice.  
Version: V1.1 date: 2024-08

