

DA340

LED visual Indicator

With independently switched 10mm jumbo LED's this unit can clearly display red, amber or green indications (model dependant). With a low current input to switch each LED independently (<1mA) & 12V DC operation, this unit is very versatile. Typical uses include remote indication of alarm system set/unset or electronic door status.

Output		
Indication	DA340	DA340-3
	10mm  Green LED	10mm  Green LED
	10mm  Red LED	10mm  Amber LED
		10mm  Red LED
Input		
Voltage	10.5 to 14V DC	
Power consumption	< 55mA	
Connection type	PCB terminal block (2mm ²)	
Independent LED trigger inputs (RD, GN, YL)	+5V < +30V DC	
Environmental		
Operating temperature	-10°C to +40°C	
Storage temperature	-20°C to +50°C	
Operating relative humidity	Maximum 95% non-condensing	
Ingress protection	DA340	DA340-IP66
	IP20	IP66
Dimensions*		
	DA340	DA340-IP66
Width	54mm	80mm
Height	110mm	140mm
Depth	25mm	55mm
Weight	< 0.05Kg	< 0.9Kg
Enclosure material	Plastic	
Finish	White	IP66 enclosure front: Clear IP66 enclosure rear: Light grey Internal PCB enclosure: White
Other		
Estimated mean time before failure (MTBF)	50,000 hours	
CE Approved	Yes	
Lid tamper	Yes	

*(+/- 2mm)