

# 24VAC external IP68 power supplies

VPSU24X1EXTe



VPSU2441EXTe



VPSU2481EXTe

## KEY FEATURES

24VAC output

IP68 external enclosure

Supplied with compression glands and mounting fixings

Supplied with additional fuses

## TECHNICAL SPECIFICATION

| Model           | VPSU2441EXTe   | VPSU2481EXTe                 |
|-----------------|--|------------------------------|
| <b>INPUT</b>    |  |                              |
| Voltage         | 230VAC Nominal (+10% / -15%)   |                              |
| Frequency       | 50Hz   |                              |
| Fuse (F5)       | T2A - 20mm 230V HRC  |                              |
| <b>OUTPUT</b>   |  |                              |
| Nominal Voltage | 24VAC (@ 230VAC input)   |                              |
| Voltage range   | 23VAC to 28VAC (On full load to off load @230VAC)                            |                              |
| Fuse            | F4A - 20mm Glass type - 230V   | F8A - 20mm Glass type - 230V |
| <b>PHYSICAL</b> |  |                              |
| Environment     | -10°C to 40°C @ up to 95% RH, IP68 external enclosure                        |                              |
| Dimensions      | 200H x 150W x 100D (mm)  | 200H x 200W x 100D (mm)      |
| Mounting holes  | 182.5 x 131 (mm)   | 181 x 181 (mm)               |
| Weight          | Approx 2Kg   | Approx 3Kg                   |
| Connections     | Mains input: Live (Brown), Neutral (Blue)                                    |                              |
| Compliance      | Low Voltage: 2014/35EU, EMC: 2104/30/EU, RoHS2: 2011/65/EU, WEEE: 2012/19/EU |                              |

## MODELS IN THIS RANGE

0785100 VPSU2441EXTe

0785130 VPSU2481EXTe



No liability will be accepted by Vista for any errors or omissions in this information | Subject to change without notice.

VPSU24XXEXTe - Version 1.1 11/24



TEL  
+44 (0) 118 912 5000

