



## Surface Magnetic Contact

*Code: GP001/AI/G2*

GP001 Type A&I | Surface Contact | Grade 2 | Aluminium | Pre-resistored

This heavy duty surface mounted magnetic contact can be used in most security systems up to grade 2 as specified in EN50131-1 and is compliant with EN50131-2-6 and environmental class II (for use indoors). It operates as a normally closed circuit going open when the magnet housing is moved away from the contact housing. This contact can be used on doors and windows to detect the unauthorised entry of an intruder. The contact is sealed to prevent access to inside of the unit.

### Features & Benefits

- High Quality Alloy Finish
- Double pole configuration
- Other resistor value available
- 57cm Armoured cable lengths
- EN50131-2-6 Grade 2
- Environmental Class II



## Security

EN50131-2-6 Grade	2
Tamper Protection	Internal

## Environmental

EN50130-5 class	Class III
IP Rating	3X
Temperature range	-10°C - +40°C

## Housing

Colour	Aluminium
Material	Aluminium
Contact Dimensions (mm)	85 x 27 x 26
Magnet Dimensions (mm)	85 x 27 x 26

## Electrical

Connection type	Wired
No. of terminals	8 Wire
Contact type	Normally Closed
Contact Material	Rhodium
Wire length (mm)	470

## Features

Mode of operation	DP, EOL/FSL
Resistor Type	A & I
Operation Axes (X, Y, Z)	Y, Z
Pull-in gap (X, Y, Z)mm	20, 30
Suitable for Double Door	Yes
Connection type	Wired
No. of terminals	8 Wire

## Mechanical

Colour	Aluminium
--------	-----------