


NDAA Compliant Motorised Varifocal IP Dome Camera

VIP-D5MP28V12IRME



KEY FEATURES

NDAA Compliant

5MP Varifocal Dome

Low light sensitive

IR up to 40m

Motorised lens

IP67 ingress and
IK10 protection

H.264/H.265 dual streaming

ONVIF compliant
ONVIF Profile S, G and T

Edge Storage -
MicroSD, up to 256GB

Corridor mode

Built-in Microphone

Cross Line and Intrusion
analytics

Vista's VIP series of IP cameras are fully NDAA compliant, allowing you peace of mind in offering one, consistent range that satisfies requirements across both private business and public sector projects.

Our VIP-D5MP28V12IRMe motorised varifocal dome comes with a simplified set of core features suitable for entry level installations. Available in 5MP, the camera can be remotely adjusted via your phone or NVR. It provides a robust, IK10 vandal resistant solution along with IP67 rating against water and dust.

The dome camera offer a minimal and subtle design, making it the ideal choice for small to medium environments, where a low key, discreet profile is required.

The camera delivers dual streams in multiple formats including H.264, so you can optimise your video settings based on application. The latest H.265 technology reduces the levels of bandwidth and storage required by the recording solution.

It includes useful analytic benefits - cross line and intrusion, and event capabilities motion detection, ultra motion detection, tampering alarm and audio detection.

Other features include an integrated motorised lens, low light technology, IR illumination to 40 metres, MicroSD card edge storage and PoE are also included.

Why not look at the rest of the VIP series of cameras and their accompanying VIP series of IP NVR recorders - also NDAA compliant.

To see Vista's complete range of IP and analogue video surveillance solutions along with accessories, please visit www.norbain.com/brands/vista.

TEL
+44 (0) 118 912 5000



* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.

TECHNICAL SPECIFICATION

Model	VIP-D5MP28V12IRMe
CAMERA	
Image Sensor	1/2.7" 5MP, CMOS
Min Illumination	Colour : 0.001 lux (F1.6, AGC ON) 0 lux with IR on
WDR	120dB WDR
Shutter Time	1/100000s-1s
Day/Night Mode	Day/Night/Auto/manual IR Cut filter
Signal/Noise	>52dB
LENS	
Focal Length	2.8 - 12mm motorised
Focus Control	Auto
Aperture	F1.6
Iris Control	Fixed
IR ILLUMINATION	
Distance wavelength	Up to 40m 850nm
VIDEO	
Max. Image Resolution	2880x1620
Primary Stream	Main Stream: 5MP (2880x1620), Max 25fps; 4MP (2560x1440), Max 25fps; 3MP (2304x1296), Max 30fps; 1080P (1920x1080), Max 30fps
Secondary Stream	Sub Stream: 720P (1280x720), Max 30fps; D1 (720x576), Max 30fps; 640x360, Max 30fps;
Video Compression	H.265, H.264, MJPEG
Privacy Masking ROI	4 masks 8 ROI
INTERFACES	
Ethernet	1 x RJ45 10M/100M
NETWORK	
ONVIF	Profile S, G and T
Network Storage	NAS, ANR
Web Browser	Minimum plug-in required IE 10. Chrome 45, Firefox 52 and Edge 79.
Security	Strong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIF
Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP, SSL/TLS
AUDIO - 2-WAY	
Built-in Mic	Yes
Audio Compression	G.711
Audio Sampling Rate Bit rate	8KHz 64Kbps
INTELLIGENT ANALYTICS	
Video Analysis	Cross line and intrusion
EVENT AND STORAGE	
Storage	MicroSD, up to 256GB
Event Trigger	Motion detection, ultra motion detection, tampering alarm and audio detection
GENERAL	
Working Condition	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Environment	IP67/IK10
Power Supply	DC 12V/2A, PoE (IEEE 802.3af)
Power Consumption	8.0W
Surge Protection	6KV
NET Dimensions Weight	Φ128 x 110mm (Ø5.0" x 3.9") 0.66kg
COMPLIANCE	
CE UKCA	EMC, RoHS & LVD
NDA	Yes

MODELS IN THIS RANGE

0935880	VIP-D5MP28V12IRMe	5MP VR Dome IR
0910280	VIP-D2MP27V135IRVRMAUAL	2MP VR Dome IR
0910290	VIP-D5MP27V135IRVRMAUAL	5MP VR Dome IR
0910300	VIP-D8MP28V12IRVRMAUAL	8MP VR Dome IR

ASSOCIATED PRODUCTS

0916510	VIP-JB03	VIP-JB03 Junction Box	
0916570	VIP-JBWM03	VIP-JBWM03 wall mount & Junction box	
0916600	VIP-PM03	VIP-PM03 Pole mount for VIP-JBWM01/02/03	
0916620	VIP-SS-02	VIP-SS-02 Sunshield for VIP-JB03/04	
0785200	VPSU12-1000e	12VDC 1A Encapsulated	
0785210	VPSU12-2000e	12VDC 2A Encapsulated	
0785220	VPSU1221EXTe	12VDC 1 x 2A, IP68	
0785240	VPSU1244EXTe	12VDC 4 x 1A, IP68	

OTHER PRODUCTS

0922960	VM215	21.5" Monitor with VGA & HDMI
0922950	VM32	32" Monitor with VGA, HDMI & BNC (CVBS)
0908420	VSW4	4 port PoE switch dual uplink
0908430	VSW8	8 port PoE switch dual uplink
0908440	VSW16	16 port PoE switch dual uplink
0908450	VSW24	24 port PoE switch dual uplink
0480540	CAT5e/UTP/305/PVC/GREY	305m Cat5e PVC cable drum - grey
0480560	CAT5e/UTP/305/LSZH/VIOLET	305m Cat5e LSZH cable drum - violet
0480580	CAT5e/UTP/305/DUCT/BLACK	305m Cat5e DUCT cable drum - black
0480610	CAT6/UTP/305/PVC/GREY	305m Cat6 PVC cable drum - grey
0480620	CAT6/UTP/305/LSZH/VIOLET	305m Cat6 LSZH cable drum - violet
0480630	CAT6/UTP/305/DUCT/BLACK	305m Cat6 DUCT cable drum - black
0853340	VCP-RJ45-Cat5-50	RJ45 Plugs x50
0853360	VCP-RJ45-Cat6-50	RJ45 Plugs x50
0853320	VSCT-RJ45	RJ45 crimp tool
0853390	VFCP-RJ45-Cat5-50	RJ45 FAST plug x50
0853410	VFCP-RJ45-Cat6-50	RJ45 FAST plug x50
0853370	VFCT-RJ45 FAST	RJ45 FAST crimp tool
0872170	DIAMOND4K	All in one CCTV/IP Cable Test Monitor

