


NDAA Compliant Motorised Varifocal IP Turret Camera

VIP-T5MP28V12IRME









KEY FEATURES

NDAA Compliant

5MP Varifocal Turret

Low light sensitive

IR up to 40m

Motorised lens

IP67 ingress protection

H.264/H.265 dual streaming

ONVIF compliant ONVIF Profile S, G and T

Edge Storage -MicroSD, up to 256GB

Corridor mode

Built-in Microphone

Cross Line and Intrusion analytics



Vista's VIP series of IP cameras are fully NDAA compliant, allowing you peace of mind in offering one, consistent range that satisfies requirements across both private business and public sector projects.

Our VIP-T5MP28V12IRMe motorised varifocal turret comes with a simplified set of core features suitable for entry level installations. Available in 5MP, the camera has an IP67 rating against water and dust. It is versatile and remotely adjustable from your phone or NVR, making it a great choice for small to medium environments.

The camera delivers dual streams in multiple formats including H.264, so you can optimise your video settings based on application. The latest H.265 technology reduces the levels of bandwidth and storage required by the recording solution.

It includes useful analytic benefits - cross line and intrusion, and event capabilities motion detection, ultra motion detection, tampering alarm and audio detection.

Other features include an integrated motorised lens, low light technology, IR illumination to 40 metres, MicroSD card edge storage and PoE are also included.

Why not look at the rest of the VIP series of cameras and their accompanying VIP series of IP NVR recorders - also NDAA compliant.

To see Vista's complete range of IP and analogue video surveillance solutions along with accessories, please visit www.norbain.com/brands/vista.



* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.

TECHNICAL SPECIFICATION

Induct International Internatinterational International Inte	Model	VIP-T5MP28V12IRMe
Image SensorI/2.7" SMP, CMOSMin IlluminationColour: 0.001 Lux (FIR, AGC on) 0 Lux withi IR onWOR20.48 WORShutter Time10.40 KORShutter Time10.40 KORSignal/Noise30.252d8Signal/Noise522d8ENS28 - Turm motorisedFocal Length4.28 - Turm motorisedAperture28 - ControlAperture10.40 KORRi LLUMINTONFIRedBistance I wavelength0.40 to 4.0m (1950nmVIEC10.40 KORWax, Image Resolution2880x1620Max, Image Resolution2880x1620Primary StreamSub Stream: 200 (1280x720), Max 30fps; 1060 (1920x1080), Max 30fps;Video Compresion11.8 KLAMAN, ADE (580 HA40), Max 25fps;Video Compresion10.4256, H244, MJREGViter20.4204x1295), Max 30fps; 1060 (1920x1080), Max 30fps;Video Compresion11.8 KLAMAN, ADE (580 HA40), Max 30fps;Video Compresion11.8 KLAMAN, ADE (580 HA10), AD		VIPTIJNEZOVIZIKNE
Min IlluminationColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onWDRI20dB WDRShutter TimeI20dB WDRDay/Night ModeDay/Night/Auto/manual IR Cut filterSignal/NoiseColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onSignal/NoiseIColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onSignal/NoiseColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onENSColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux with IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux With IR onFocal LengthColour: 0.001 Lux (F16, AGC on) 0 Lux With IR onFor Hux (F16, AGC on) 0 Lux (F16, AGC on) 0 Lux With IR onSolor (F16, F16, F16, F16, F16, F16, F16, F16,		1/2 7" EMD CMOS
WDR120dB WDRShuter Time (N000005-IsDayNight MoleDayNight MoleDayNight MoleDayNight MoleSold Ent Signal/Noise Sold EntFocal Length(Althouse Althouse Altho		
Shutter TimeI/100000s-1sDay/Night/ModeDay/Night/Jut//manual IR Cut filterSignal/NoiseS268JenseS268Focal LengthC.B.Y.Focal LengthC.B.Y.Focal LengthC.B.Y.Focal LengthG.C.B.Y.Iris ControlJ.B.Y.Iris ControlJ.B.Y.Iris ControlJ.B.Y.Iris LiumiNATIONJ.B.Y.VIECOJ.B.Y.VIECOJ.B.Y.Max. Image ResolutionS260.A.S.Y.S. (Story MAX 250p. Story Cl22Ox1080), Max 250p.Scondary StreamSub Stream: SDM (2880.Xi620), Max 250p. Story Cl22Ox1080), Max 301ps.Scondary StreamSub Stream: 720 (1800.YZO), Max 301ps. DI (720.YZO), Max 301ps.Video CompressionG.D.G.Y.S.W.S.Y.C.S.M.S. (Story Cl22Ox1080), Max 301ps.Video CompressionSub Stream: 720 (1800.YZO), Max 301ps. DI (720.YZO), Max 301ps.Video CompressionSub Stream: 720 (1800.YZO), Max 301ps.Video CompressionSub Stream: 720 (1800.YZO), Max 301ps.Video CompressionStrong password, HTTPS, Algest authentication for RTSP, TLS 12, WSSE and diget 20.NVIFUmbi, HTTP, HTTPS, SMTP, SNMP, AS, ANRVeb BrowserStrong password, HTTPS, diget authentication for NVIFPortocolIPV4, IPV6, JGMP, ICMP, ARP, TCD, UDP, DCH, CHP, RTSP, RTCP, DNS, DDNS, NTP, FTF, Authentication for ONVIFVatio CompressionG.C.C.YZ, FL, HO'FS, Humildy, SSS, RH (non-condensing)Audio Samgling Ret Bit 70Storg Authentication, transpring alarm and audio detectionVENT AND STORAELUmbi, HTTP, HTTPS, Cl22FF		
Day,Night ModeDay/Night/Auto/manual IR Cut filterSignal/NoiseS52dBLENSFocal Length2.8 - 12mm motorisedFocus ControlAutoApertureF1.6Iris ControlExedIris ControlUto 40m I 850mIris ControlUb to 40m I 850mVIECOVIECOWiterStream: SMP (2880x1620, Max 25frs; 4MP (2560x1440), Max 25frs;Primary StreamStream: SMP (2880x1620, Max 20frs; 101/20x576), Max 30frs;Video CompressionLACES, Max 20frs; 101/20x576), Max 30frs;Video CompressionSub Stream: 720P (1280x70), Max 30frs; 101/20x576), Max 30frs;Video CompressionLACES, LAEA, MJPEGPrivacy Masking I ROIStroam 30frs;Noter StorageNASA, SANNetwork StorageMinimum plug-in required IE 10. Chrome 45, Firefox S2and Edge 79.Storage Storage Jassword, HTPES, digest authentication for RTSP. TLS 12, WSE and digestAudio CompressionG.711ProtocolIPv4, IPv6, JGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTPE, SMP, SMP, SMP, RSN, PTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTPE, SMP, SMP, SMP, RSN, PTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTP, SMP, SMP, SMP, RSN, PTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTP, SMP, SMP, SMP, RSN, PTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTP, SMP, SMP, SMP, RSN, PTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTP, SMP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTP, SM		
Signal/Noise>52dBLENSFocal Length2.8 -12m motorisedFocus ControlAutoApertureF1.6Iris ControlEixedIris ControlUp to 40m 850nmVIDEOVideo (1990) Max 25fps; 1049/ (2560x1440), Max 25fps;Max, Irnage Resolution2880x1820Primary StreamMain Stream: SMP (2880x1820), Max 25fps; 1089/ (2560x140), Max 25fps;Video CompressionH2258, 1246, MJPEGPrivacy Masking ROI4 masks 8 ROIINTERACESEithermetEthermet1 x RJ45 10M/100MNETWORKVideo CompressionONVIFProfile S, G and TNetwork StorageMinimum plug-in required IE ID. Chrome 45, Firefox 52and Edge 79.SecurityStrong password, HTTR; digest authentication for RTSP, TLS 12, WSE and digest authentication for GONVIFProtocolIPv4, IPv6, IGMP, ICMP, APR, TCP, UDP, DHCP, RTSP, RTCP, DMS, DDNS, NTP, FTP, UPn9, HTTP, HTTPS, SMP, SMP, SMP, SMP, SMP, SMP, SMP, S		
LINS Focal Length 2.8 - 12mm motorised Focus Control Auto Aperture F16 Iris Control Fixed Iris Control Fixed Iris Control Up to 40m 850nm VIDEO 2880x1620 Max. Image Resolution 2880x1620 Max. Image Resolution 2880x1620 Secondary Stream Sub Stream: SMP (2880x1620, Max 30fps; 1080P (1920x1080), Max 30fps; Secondary Stream Sub Stream: SMP (2800x1620, Max 30fps; 1080P (1920x1080), Max 30fps; Secondary Stream Sub Stream: 720P (1260x720), Max 30fps; 1080P (1920x1080), Max 30fps; Secondary Stream Sub Stream: 720P (1260x720), Max 30fps; 1080P (1920x1080), Max 30fps; Iritary Maxing IROI 4 masks J 8 ROI IntterFACES InterfAceS Ethernet 1 x RJ45 10M/100M NEtwork Strong password, HTTPS, diget authentication for RTSP, RTLP, SL2, WSSE and diget 30 Security Strong password, HTTPS, SHTP, SHTP, SHTP, STLS 2, WSSE and diget 30 Audio Compression G.711 Audio Sampling Rate Bit rate 8KH2 64Kbps Inteleint MAULCEENT		
Focal Length2.8 - 12mm motorisedFocas ControlAutoApertureF1.6Isis ControlF1.6Isis ControlUp to 40m 850mmIsis ControlUp to 40m 850mmVIEEOMax. Image ResolutionVIEEO2880x1620Primary StreamMain Stream: SMP (2880x1620, Max. 25fps: 3MP (2560x1440, Max 25fps); 3MP (230Ax1296), Max 30fps: 1060P (1920x1080), Max 30fps; 640x360, Max 30fps:Video CompressionCatego (120, Vax), Max 30fps; 1060P (1920x1080), Max 30fps; 640x360, Max 30fps;Video CompressionCatego (120, Vax), Max 30fps; 1070x376), Max 30fps; 640x360, Max 30fps;Video Compression1 x RJ45 10M/100MHTERACESTo X145 10M/100MEthernet1 x RJ45 10M/100MNETWORKProfile S, G and TNetwork StorageMinimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79.SecurityStrong password, HTTPS, digest authentication for RTSP, TLS 12, WSE and digest authentication for ONVIFProtocolIPv4, IPv6, IGMP, ICMP, ARF, DCP, UDP, DCF, TR, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPRP, HTTP, SMTP, S	÷ .	~3200
Cosus Control Auto Aperture I. Auto Aperture FL6 Iris Control FL6 Iris Control FL6 Iris Control FL6 Iris Control FL9 Distance wavelength Up to 40m 850nm VIDEO Z880x1620 Max. Image Resolution 2880x1620 Max. Image Resolution Sub Stream: 720P (280x702), Max 30fps; 10/20x763), Max 30fps; Secondary Stream Sub Stream: 720P (280x720, Max 30fps; 10/20x763), Max 30fps; Secondary Stream Sub Stream: 720P (280x720, Max 30fps; 10/20x763), Max 30fps; Video Compression G40x360, Max 30fps; 10/20x763), Max 30fps; Video Compression A masks I 8 R0I NETWORK ONVIF ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox S2and Edge 79. Security Strong password, HTTP, Sty, Giesa 410 threction for ONVIF Protocol IPv4, IPv6, IGMP, ICMP, APR, PCP, IDP. DPC, PTP, RTSP, RTP, DNS, DNS, NTP, FTP, EDP, IDV1, IDV		2.8 × 12mm motorised
ApertureF1.6Iris ControlFixedIris ControlFixedIris LLUMINATIONUp to 40m 850nmDistance I wavelengthUp to 40m 850nmVIDEO2880x1620Max. Image Resolution2880x1620, Max 30fps; 1080P (1920x1080), Max 30fps; 3MP (2360x1440), Max 30fps; 10400,	-	
Irs Control Fixed IR LLUMINATION Up to 40m 850nm Distance wavelength Up to 40m 850nm VIDEO 2880x1620 Max. Image Resolution 2880x1620, Max 25fps; AMP (2560x1440), Max 25fps; SMP (2560x1440), Max 25fps; SMP (2560x1440), Max 25fps; SMP (2560x1440), Max 25fps; SMP (2560x140), Max 30fps; SMP (250x1900P, 102x01500), Max 30fps; Secondary Stream Sub Stream: 720P (1280x720), Max 30fps; DI (720x576), Max 30fps; SMP (250x140), Max 30fps; DI (720x576), Max 30fps; DI (720x576), Max 30fps; SMP (250x140), Max 30fps; DI (720x576), Ma		
IR ILLUMINATION Distance wavelength Up to 40m 850nm VIDEO 2880/1620 Max. Image Resolution 2880/1620, Max 25fps; 4MP (2560x1440), Max 25fps; 3MP (2304x1296), Max 30fps; 1060P (1920x1600), Max 30fps; Secondary Stream Sub Stream; 720P (280x760), Max 30fps; 1060P (1920x1600), Max 30fps; Secondary Stream Sub Stream; 720P (280x720), Max 30fps; 1070x576), Max 30fps; Secondary Stream Sub Stream; 720P (280x720), Max 30fps; 10720x576), Max 30fps; Video Compression H.265, H.264, MJPEG Privacy Masking R01 4 masks 8 R01 INTERFACES Ethernet Ethernet 1 x RJ45 10M/100M NETWORK ONVIF ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTTPS, digest authentication for NVIF Protocol IPV4, IPV6 JGMR JCMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPR, HTTP, STMP, Gos, RTMP, SSL/TLS JUDIO - 2-WAY UPR, HTTP, HTTPS, SMTP, SNMP, Gos, RTMP, SSL/TLS JUDIO - 2-WAY Strong Banding Rate Btr rate Storage MicroSD, up to 256GB Event Trigger <td></td> <td></td>		
Distance wavelengthUp to 40m 850nmVIDEOMax. Image Resolution2880x1620Primary StreamMain Stream: SMP (2880x1620, Max 25fps; AMP (2560x1440), Max 25fps; 3MP (2304x1296), Max 30fps; 1080P (1920x1080), Max 30fps; 640x360, Max 30fps; 101 (720x576), Max 30fps; 640x360, Max 30fps; 101 (720x576), Max 30fps; 		Fixed
VIDEOMax. Image Resolution2880x1620Main Stream: SMP (2880x1620), Max 25fps; 4MP (2560x1440), Max 25fps; 3MP (2360x1260), Max 30fps; 1060 (1920x1080), Max 30fps;Secondary StreamSub Stream: 720P (1280x720), Max 30fps; 101 (720x576), Max 30fps; 640x360, Max 30fps; D1 (720x576), Max 30fps;Video CompressionH.265, H.264, M.PEGPrivacy Masking R014 masks 8 R01INTERACESInterferenceEthernet1 x R.J45 10M/100MNETWORKProfile S, G and TONVIFProfile S, G and TNetwork StorageMinimum plug-in required IE 10. Chrome 45, Firefox S2and Edge 79.SecurityStrong password, HTTPS, digest authentication for RTSP, TLS 12, WSSE and digest authentication for ONVIFProtocolIPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPn, HTTP, SHTP, SNM, QoS, RTMP, SSL/TLSAudio CompressionG.711Audio CompressionG.711Audio CompressionGross line and intrusionEVENT AND STORAGEVesStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGentesLVesVorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: s45% RH (non-condensing)EnvironmentIP67Power Consumption75WSurge ProtectionGKVNET Dimensions Weight4129 x 110mm (d51'x 4.3") 0.66kgCOMPLIACEEUKCAEMC, ROKS & LVD		Lin to 40m SE0nm
Max. Image Resolution2880x1620Primary StreamMain Stream: SMP (2880x1620), Max 25fps; 4MP (2560x140), Max 25fps; 3MP (2304x1296), Max 30fps; 10 (220x576), Max 30fps; 640x360, Max 30fps; 10 (720x576), Max 30fps; 97 (230x576), Max 30fps; 10 (720x576), Max 30fps; 97 (230x576), Max 30fps; 10 (720x576), Max 30fps; 97 (230x576), Max 30fp; 97 (230x576), Max 30fp;<		op to 4011 8501111
Primary Stream Main Stream: SMP (2880x1620), Max 25fps; 4MP (2560x1440), Max 25fps; 3MP (2304x1296), Max 30fps; 1080P (1920x1080), Max 30fps; 640x360, Max 30fps; Secondary Stream Sub Stream: 720P (280x720), Max 30fps; DI (720x576), Max 30fps; 640x360, Max 30fps; Video Compression H.265, H.264, MJPEG Privacy Masking R0 4 masks 8 R0 INTERFACES Ethernet ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTTPS, digest authentication for RTSP, TL 5 12, WSSE and digest authentication for ONVIF Protocol IPv4, IPv6, IGMP, ICMP, ARP, TCP, UOP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SMTP, SMP, GoS, RTMP, SSL/TLS AUDIO - 2-WAY Storage Yes Built-in Mic Yes Storage INTELLGENT ANALYTICS Yes Storage Video Analysis Cross line and intrusion EVENT AND STORAGE Storage Storage Motion detection, ultra motion detection, tampering alarm and audio detection Event Trigger Motion detection, ultra motion detection, tampering alarm and audio detection Genveral IP67 P		2000/1620
Primary stream3MP (2304x1296), Max 30fps; ID(200K1980), Max 30fpsSecondary StreamSub Stream: 720P (1280X720), Max 30fps; ID (720X57), Max 30fps;Video Compression4Privacy Masking I ROI4INTERFACES1Ethernet1 x RJ45 IOM/IOOMINTERFACES1ONVIF0ONVIF0Network StorageMinimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79.SecurityStrong password, HTTPS, digest authentication for RTSP, TLS 12, WSSE and digest authentication for ONVIFProtocolIPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, INS, DDNS, NTP, FTP, UPNP, HTTP, HTTPS, SMTP, SMMP, QoS, RTMP, SSL/TLSAudio CompressionGAudio CompressionGINTELLGENT ANALYTCSVideo AnalysisCross line and intrusionEvent And StorageMicroSD, up to 256GBEvent And StorageMicro GC (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F - 140°F), Humidity: s95%, RH (non-condensing)Environment-30°C - 60°C (-22°F -	Max. Image Resolution	
Secondary Stream 640x360, Max 30fps; Video Compression H.265, H.264, MJPEG Privacy Masking R0 4 masks 8 R0 INTERFACES Ethernet Ethernet 1 x RJ45 10M/100M NETWORK ONVIF ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIF Protocol IPv4, IPv6, JGMP, ICMP, AER, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UDP, HTTP, SMTP, SNMP, QoS, RTMP, SSL/TLS Audio Compression G.711 Audio Sampling Rate Bit rate BKTC 9 Video Analysis Cross line and intrusion EVENT AND STORAGE Storage Event Trigger Motion detection, ultra motion detection, tampering alarm and audio detection GENERAL IP67 Power Consumption -30°C - 60°C (-22°F - 140°F), Humidity: s95% RH (non-condensing) Environment IP67 Power Supply Cho°C (-22°F - 140°F), Humidity: s95% RH (non-condensing) Environment IP67 Power Consum	Primary Stream	3MP (2304x1296), Max 30fps; 1080P (1920x1080), Max 30fps
Privacy Masking ROI 4 masks 8 ROI INTERFACES 1 x RJ45 10M/100M Ethernet 1 x RJ45 10M/100M NETWORK Profile S, G and T ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIF Protocol IPv4, IPv6 (IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPP, HTP, HTTPS, SMTP, GON, STMP, SL, TLS Audio Compression G.711 Audio Sampling Rate Bit rate BKHz 64Kbps INTELLIGENT ANALYTICS Video Analysis Video Analysis Cross line and intrusion EVENT AND STORAGE MicroSD, up to 256GB Event Trigger Motion detection, ultra motion detection, tampering alarm and audio detection GRNRAL -30°C - 60°C (-22°F - 140°F), Humidity: a95% RH (non-condensing) Environment -30°C - 60°C (-22°F - 140°F), Humidity: a95% RH (non-condensing) Environment -50°C A0°C (-22°F - 140°F), Humidity: a95% RH (non-condensing) Environment FIPG Power Supply Choro C (-22°F - 140°F), Humidity: a95% RH (Secondary Stream	
INTERFACES Ethernet 1 x RJ45 10M/100M NETWORK ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIF Protocol IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPNP, HTTP, HTTPS, SMPB, QS, RTMP, SSL/TLS AUDIO - 2-WAY Built-in Mic Yes Audio Compression G.711 Audio Sampling Rate Bit rate 8KHz 64Kbps INTELIGENT ANALYTICS Video Analysis Cross line and intrusion EVENT AND STORAGE Event Trigger Motion detection, ultra motion detection, tampering alarm and audio detection General Yorking Condition -30°C - 60°C (-22°F - 140°F), Humidity: a95% RH (non-condensing) Environment IP67 Power Consumption 7.5W Surge Protection GKV NET Dimensions Weight 4129 × 110mm (Ø5.1° x 4.3° 0.66kg COMULIANCE EUC LANC	Video Compression	H.265, H.264, MJPEG
Ethernet 1 x RJ45 10M/100M NETWORK Profile S, G and T ONVIF Profile S, G and T Network Storage Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTPS, digest authentication for RTSP, TLS 12, WSSE and digest authentication for NVIF Protocol IPV4, IPV6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPP, UPP, HTTP, HTTPS, SMTP, SMTP, SMTP, SMTP, SSL/TLS Audio Compression G.711 Audio Sampling Rate Bit rate 8KHz 64Kbps INTELLIGENT ANALYTICS Event Trigger Video Analysis Cross line and intrusion EVENT AND STORAGE Event Trigger Storage MctoroSD, up to 256GB </td <td>Privacy Masking ROI</td> <td>4 masks 8 ROI</td>	Privacy Masking ROI	4 masks 8 ROI
NETWORK ONVIF Profile S, G and T Network Storage NAS, ANR Web Browser Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79. Security Strong password, HTTPS, digest authentication for RTSP, TLS 12, WSSE and digest authentication for ONVIF Protocol IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPn, HTTP, SMTP, SMTP, SMTP, SMTP, SSL/TLS Audio Compression G.711 Audio Sampling Rate Bit rate 8KHz 64Kbps INTELLIGENT ANALYTICS Video Analysis Video Analysis Cross line and intrusion Event Trigger Motion detection, ultra motion detection, tampering alarm and audio detection GENERAL Vorking Condition Prower Supply G0°C - 60°C (-22°F - 140°F), Humidity: ±95% RH (non-condensing) Environment IP67 Power Consumption -30°C - 60°C (-22°F - 140°F), Humidity: ±95% RH (non-condensing) Environment IP67 Power Supply DC 12V/2A, PoE (IEEE 802.3af) Power Consumption 7.5W Surge Protection 6KV NET Dimensions Weight Ф129 x 110mm (051" x 4.3") 0.66kg	INTERFACES	
ONVIFInterfaceNetwork StorageMinimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79.SecurityStrong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIFProtocolIPv4, IPv6, JGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UDP, DHCP, RTP, SNMP, QoS, RTMP, SSL/TLSAuDio - 2-WAYUPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP, SSL/TLSBuilt-in MicYesAudio CompressionG.711Audio Sampling Rate Bit rate8KHz 64KbpsINTELLIGENT ANALYTICSVideo AnalysisVideo AnalysisCross line and intrusionEVENT AND STORAGEMotion detection, ultra motion detection, tampering alarm and audio detectionGenERALVorking ConditionVorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: s95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions Weight4129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMCACE UKCAEMC, RoHS & LVD	Ethernet	1 x RJ45 10M/100M
Network StorageNAS, ANRWeb BrowserMinimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79.SecurityStrong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIFProtocolIPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, SMTP, SMTP, SMP, QoS, RTMP, SSL/TLSAUDIO - 2-WAYBuilt-in MicYesAudio CompressionG.711Audio Sampling Rate I Bit rate8KHz I 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALIP67Power SupplyOC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEVEN KGACE UKCAEMC, RoHS & LVD	NETWORK	
Web BrowserMinimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79.SecurityStrong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIFProtocolIPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPNP, HTTP, SMTP, SMTP, SMP, QoS, RTMP, SSL/TLSAUDIO - 2-WAYBuilt-in MicYesAudio CompressionG.711Audio Sampling Rate I Bit rate8KHz I 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALIP67Vorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: s95% RH (non-condensing)EnvironmentIP67Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEVEN KGACE UKCAEMC, RoHS & LVD	ONVIF	Profile S, G and T
Security Strong password, HTTPS, digest authentication for RTSP, TLS 1.2, WSSE and digest authentication for ONVIF Protocol IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, SMTP, SMTP, SMTP, SMTP, SMTP, SSL/TLS AUDIO - 2-WAY Built-in Mic Yes Audio Compression G.711 Audio Sampling Rate Bit rate BKHz 64Kbps INTELLIGENT ANALYTICS Video Analysis Cross line and intrusion EVENT AND STORAGE Storage MicroSD, up to 256GB Event Trigger Motion detection, ultra motion detection, tampering alarm and audio detection GENERAL Working Condition -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing) Environment IP67 Power Supply DC 12V/2A, PoE (IEEE 802.3af) Power Consumption 7.5W Surge Protection 6KV NET Dimensions Weight Φ129 x 110mm (Ø5.1" x 4.3") 0.66kg COMPLIANCE EMC, RoHS & LVD	Network Storage	NAS, ANR
Securityauthentication for ONVIFProtocolIPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP, SSL/TLSAUDIO - 2-WAYBuilt-in MicYesAudio CompressionG.711Audio Sampling Rate Bit rateBKH2 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: s95% RH (non-condensing)EnvironmentIP67Power Consumption7.5WSurge ProtectionGKVNET Dimensions WeightΦ129 x 110mm (ØS.1" x 4.3") 0.66kgCOMPLIANCEEVC, RoHS & LVD	Web Browser	Minimum plug-in required IE 10. Chrome 45, Firefox 52and Edge 79.
ProtocolUPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP, SSL/TLSAUDIO - 2-WAYBuilt-in MicYesAudio CompressionG.711Audio Sampling Rate Bit rate8KHz 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEStorageMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: s95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCE UKCAEMC, RoHS & LVD	Security	
Built-in MicYesAudio CompressionG.711Audio Sampling Rate Bit rate8KHz 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: ±95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	Protocol	
Audio CompressionG.711Audio Sampling Rate Bit rate8KHz 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEStorageMciroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: £95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	AUDIO - 2-WAY	
Audio Sampling Rate Bit rate8KHz 64KbpsINTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERAL-30°C - 60°C (-22°F - 140°F), Humidity: ±95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø51" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	Built-in Mic	Yes
INTELLIGENT ANALYTICSVideo AnalysisCross line and intrusionEVENT AND STORAGEStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	Audio Compression	G.711
Video AnalysisCross line and intrusionEVENT AND STORAGEStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	Audio Sampling Rate Bit rate	8KHz 64Kbps
EVENT AND STORAGEStorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERAL-30°C - 60°C (-22°F - 140°F), Humidity: ±95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	INTELLIGENT ANALYTICS	
StorageMicroSD, up to 256GBEvent TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: ±95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCEEMC, RoHS & LVD	Video Analysis	Cross line and intrusion
Event TriggerMotion detection, ultra motion detection, tampering alarm and audio detectionGENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCECE UKCAEMC, RoHS & LVD	EVENT AND STORAGE	
GENERALWorking Condition-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCECE UKCAEMC, RoHS & LVD	Storage	MicroSD, up to 256GB
Working Condition-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCECE UKCAEMC, RoHS & LVD	Event Trigger	Motion detection, ultra motion detection, tampering alarm and audio detection
EnvironmentIP67Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCECE UKCAEMC, RoHS & LVD	GENERAL	
Power SupplyDC 12V/2A, PoE (IEEE 802.3af)Power Consumption7.5WSurge Protection6KVNET Dimensions WeightФ129 x 110mm (Ø5.1" x 4.3") 0.66kgCOMPLIANCECE UKCAEMC, RoHS & LVD	Working Condition	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Power Consumption 7.5W Surge Protection 6KV NET Dimensions Weight Ф129 x 110mm (Ø5.1" x 4.3") 0.66kg COMPLIANCE CE UKCA EMC, RoHS & LVD	Environment	IP67
Surge Protection 6KV NET Dimensions Weight Ф129 x 110mm (Ø5.1" x 4.3") 0.66kg COMPLIANCE CE UKCA EMC, RoHS & LVD	Power Supply	DC 12V/2A, PoE (IEEE 802.3af)
NET Dimensions Weight Ф129 x 110mm (Ø5.1" x 4.3") 0.66kg COMPLIANCE EMC, RoHS & LVD	Power Consumption	7.5W
COMPLIANCE CE UKCA EMC, RoHS & LVD	Surge Protection	6KV
CE UKCA EMC, RoHS & LVD	NET Dimensions Weight	Ф129 x 110mm (Ø5.1" x 4.3") 0.66kg
	COMPLIANCE	
NDAA Yes	CE UKCA	EMC, RoHS & LVD
	NDAA	Yes

MODELS IN THIS RANGE

0935890	VIP-T5MP28V12IRMe
5MP 2.8-12m	nm Turret
0910330	VIP-T5MP27V135IRM
5MP 2.7-13.5	mm Turret
0910340	VIP-T8MP28V12IRM
8MP 2.8-12m	nm Turret

ASSOCIATED PRODUCTS

0916510 VIP-JB03 VIP-JB03 Junction Box	Θ
0916570 VIP-JBWM03 VIP-JBWM03 wall mount & Junction box	-
0916600 VIP-PM03 VIP-PM03 Pole mount for VIP-JBWM01/02/03	
0916620 VIP-SS-02 VIP-SS-02 Sunshield for VIP-JB03/04	
0785210 VPSU12-2000e 12VDC 2A Encapsulated	
0785220 VPSU1221EXTe 12VDC 1 x 2A, IP68	

OTHER PRODUCTS

0922960 VM215 21.5" Monitor with VGA & HDMI
0922950 VM32 32" Monitor with VGA, HDMI & BNC (CVBS)
0908420 VSW4 4 port PoE switch dual uplink
0908430 VSW8 8 port PoE switch dual uplink
0908440 VSW16 16 port PoE switch dual uplink
0908450 VSW24 24 port PoE switch dual uplink
0480540 CAT5e/UTP/305/PVC/GREY 305m Cat5e PVC cable drum - grey
0480560CAT5e/UTP/305/LSZH/VIOLET305m Cat5e LSZH cable drum - violet
0480580 CAT5e/UTP/305/DUCT/BLACK 305m Cat5e DUCT cable drum - black
0480610CAT6/UTP/305/PVC/GREY305m Cat6 PVC cable drum - grey
0480620 CAT6/UTP/305/LSZH/VIOLET 305m Cat6 LSZH cable drum - violet
0480630 CAT6/UTP/305/DUCT/BLACK 305m Cat6 DUCT cable drum - black
0853340 VCP-RJ45-Cat5-50 RJ45 Plugs x50
0853360 VCP-RJ45-Cat6-50 RJ45 Plugs x50
0853320 VSCT-RJ45 RJ45 crimp tool
0853390 VFCP-RJ45-Cat5-50 RJ45 FAST plug x50
0853410 VFCP-RJ45-Cat6-50 RJ45 FAST plug x50
0853370 VFCT-RJ45 FAST RJ45 FAST crimp tool
0872170 DIAMOND4K All in one CCTV\IP\Cable Test Monitor

vista