

SOINT2 / SOINT2 HI-LO

EN Grade 3 Internal Sounder



FIRE & SECURITY



The SOINT2 sounder is supplied in a sleek white low profile louvre-free housing that will blend discreetly into any surrounding.

The SOINT2 HI-LO low profile housing contains a multi tone sounder, with separate inputs for exit time and alarm sound.

Options:

SOINT2/WH

Electronically driven speaker, Tampered

SOINT2/WH/HI-LO

Electronically driven speaker, Tampered
with selectable sound output

Specifications

	SOINT2	SOINT2 HI-LO
Sounder type	16 Ohm speaker	16 Ohm speaker
Voltage	6 - 15 vdc	12 - 15 vdc
Current	250mA	300mA Hi / 33mA Lo
Sound output at 1m	110	110 Hi / 90 Lo
Frequency Range	1.2 - 1.8 kHz	1.2 - 1.8 kHz
Timer	N/A	N/A
Tamper protection	Wall / Cover	Wall / Cover
Material	ABS	ABS
Visual indication	LED	LED
Size	w: 100mm h: 155mm d: 48mm	w: 100mm h: 155mm d: 48mm
EN Grade 3	3	3



Contact us:

Phone:

Tel: +44(0)151 6061000

Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk

Email: info@cqr.co.uk



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

