

DOME JUNCTION BOX – DJBW

EXTERNAL / INTERNAL SPACER FOR STATIC DOMES



KEY FEATURES

Simple installation

Allows the connection cables to be hidden within

Top plate

Allows mounting of internal domes and external bullet cameras.

The DJBW junction box is designed to make the installation on Vista domes simpler, by providing a spacer that allows the connection cables to be hidden within.

The DJBW is supplied with a top plate to allow the mounting of internal domes and Vista bullet cameras.

For External applications this plate is not required, the external domes are mounted directly to the main casing.

COMPATIBLE CAMERAS (INTERNAL OR EXTERNAL APPLICATION)

DJBW	
VVRD28V12MHDAW	VBC28V12MHDAW
VVRD28V12MHD AIRW	VK2-2MPXBIR28V12Ms
VVRD28V12MHD AIRSW	VK2-4MPXBIR28V12Ms
VK2-2MPXVRD37IR	VFDA28V12HDA -xxx
VK2-2MPXVRD28V12M	VP-HDA20-SMW
VK2-4MPXVRD28V12M	VP-HD20IR-SMW
VK2-4KXVRD28V12M	VK2-HD20-SMW
VK2-2MXVFDIR28V12M	VK2-HD23IR-SMW



TEL
+44 (0) 118 912 5000



TECHNICAL SPECIFICATION

Model	DJBW
Dimensions	Diameter 147mm, height 40mm (including front plate)
Mounting holes	4 x 6mm at 121mm diameter (supplied sealing o-rings must be used)
External dome mounting holes	4 x 3mm at 121mm diameter (4 x 3mm machine screws supplied)
Internal dome mounting	Face plate with pre-drilled 3mm threaded holes (screws supplied)
Cable entry	2 x 3/4" conduit ports rear and side entry
Material	Aluminium
Colour	White
IP rating	IP66 (note camera options)

MODELS IN THIS RANGE

0811180 DJBW
Junction box



No liability will be accepted by Vista for any errors or omissions in this information | Subject to change without notice.

DS - DJBW - Version 1



TEL
+44 (0) 118 912 5000

