

AXIS Surveillance Card 64 GB

High endurance microSDXC™ card

AXIS Surveillance Card 64 GB is a high performing edge storage solution optimized for video surveillance. Edge storage enables flexible storage solutions such as de-centralized video recording and may eliminate the need of an onsite server, DVR or NVR. In applications with bandwidth limitations, live video can be viewed in low resolution, while high resolution video is recorded locally on AXIS Surveillance Card 64 GB. Combined with Axis Zipstream technology, even high resolution video can be recorded effectively local on AXIS Surveillance Card 64 GB, both for primary storage or as redundancy for failover recording in case of lost connections.

- > [Optimized for surveillance cameras](#)
- > [Health monitoring ready](#)
- > [SD card adapter included](#)
- > [Axis 3-year warranty](#)



AXIS Surveillance Card 64 GB

SD card		Storage conditions	-40 °C to 85 °C (-40 °F to 185 °F)
Form factor	microSDXC™ with SD™ card adapter ^a	Sustainability	PVC free
Packaging	The microSDXC™ card and SD™ card adapter are delivered in a jewel case	Approvals	EN 55022 Class B, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, RCM AS/NZS CISPR 22 Class B, VCCI Class B
Color	White	Compatibility	All Axis products with SD card support.
Capacity	64 GB ^b	Warranty	Axis 3-year warranty, see www.axis.com/warranty
Class	Class 10 (C10) and UHS Speed Class 1 (U1)	a. <i>SanDisk is a trademark of SanDisk Corporation, registered in the United States and other countries. microSDXC and SD marks and logos are trademarks of SD-3C, LLC.</i> b. <i>1GB=1,000,000,000 bytes. Actual user storage less.</i>	
Transfer speed read/write	50 – 80 MB/s read/write	Environmental responsibility: www.axis.com/environmental-responsibility	
Card dimensions	microSDXC™ card: 15 mm x 11 mm x 1.0 mm (0.59 in x 0.43 in x 0.04 in) SD™ adapter: 24 mm x 32 mm x 2.1 mm (0.94 in x 1.26 in x 0.08 in)		
Operating conditions	-25 °C to 85 °C (-13 °F to 185 °F)		