

# DA369

**12V DC & 16V AC Power supply**  
*Within a mild steel enclosure*

A power supply with 1 x 3A 12V DC output. This unit can house and charge one VRLA battery up to 7Ah capacity. There is also 1 x 5A 16V AC output. The DA369 is ideal for use where a DC supply is required for a controller and an AC supply is required for a door release.

| Output 1                                   |   |
|--|---|
| Voltage                                    | 12V DC (13.7V)  |
| Current                                    | Maximum 3A  |
| Connection type                            | PCB terminal block (2.5mm <sup>2</sup> )  |
| Fused                                      | 20 x 5mm 3A quick blow glass fuse   |
| Output 2                                   |   |
| Voltage                                    | 16V AC  |
| Current                                    | Maximum 5A  |
| Connection type                            | PCB terminal block (2.5mm <sup>2</sup> )  |
| Input                                      |   |
| Voltage                                    | 230V AC @ 50Hz (+/- 10%)  |
| Power consumption                          | < 158VA   |
| Connection type                            | 10mm <sup>2</sup> internal terminal block (3 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup> ) |
| Fused                                      | 5A Mains fuse (BS1362)  |
| Mains on indication                        | LED indication  |
| Environmental                              |   |
| Operating temperature                      | -10°C to +40°C  |
| Storage temperature                        | -20°C to +50°C  |
| Operating relative humidity                | Maximum 95% non-condensing  |
| Dimensions*                                |   |
| Width                                      | 266mm   |
| Height                                     | 237mm   |
| Depth                                      | 80mm  |
| Weight                                     | < 3.65Kg  |
| Enclosure material                         | Mild steel  |
| Finish                                     | Powder coated RAL9016 (white)   |
| Other                                      |   |
| Estimated operations before failure (MTBF) | 50,000 hours  |
| CE Approved                                | Yes   |
| Lid tamper                                 | Yes   |
| Recommended battery size                   | 7Ah VRLA  |

\*(+/- 2mm)