

PSI Displays Ltd




Suite C2, Butts Business Centre, Butts Road, Chiseldon, Swindon, Wiltshire, SN4 0PP. UK.

Tel: +44 (0) 1793 740456

e-mail: sales@psidisplays.co.uk Website www.psidisplays.co.uk

AHD/TVI LCD Colour Monitor Model No. L140AT

10.4" TFT LCD Colour Digital Monitor with LED back Light, AHD/TVI In/Out, HDMI, DVI, VGA, Audio In and Out via Speaker, I/R Remote Control. **Options:** 19" Rack mounting, Touch Screen, Glass Front. Other sizes available.



19" Rack mount option.



Main Features:

- Resolution: 1024 x 768
- Picture Ratio: 4:3
- Brightness: 350 cd/m2 – LED Back Light
- Contrast Ratio: 900:1
- Inputs: AHD/TVI, HDMI, DVI, VGA, Audio.
- Outputs: AHD/TVI, Earphone.
- Mounting: VESA 75 or 100, Key Hole, Stand.
- 3D De-Interlaced Technology & Comb Filter.
- Anti-blur/image auto. • Fast Response time.
- Slim Aluminium cabinet in Black.
- Speaker 2 Watts max.

The L104AT with TFT technology offers Professional sharp images coupled with a high contrast ratio of 900:1 and high Brightness giving superb pictures. AHD/TVI In/Out, HDMI, DVI. VGA and Audio makes this is a truly versatile Monitor. Also boasting various mounting options and finished in a Smart tough Aluminium Metal housing. This compact unit is ideal for Multimedia Video and Surveillance system applications.

SPECIFICATIONS:

- Active area: 211.2 x 158.4 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 8/8 ms (Tr/Tf). • Viewing angle: Left/Right: 75°, Up/ Down 75°.
- Controls/Indicators: Front: On LED, I/R sensor, Rear: Source, Menu, Item, Up, Down, Power.
- Power Source: 12V DC, 1.16 Amp, 14 Watts approx. AC Adaptor: 100-240 Vac 50/60Hz 1.5Amp.
- Dimensions: 266 x 213.3 x 42.4 (56.9 with stand). Carton: 335 x 290 x 110 (WxHxD)mm.
- Weight: Unit: 2.08 Kgms, Carton: 3.10 Kgms. • Temp: Operation: 0°C~40°C, Storage: -20~ 60°.

Connections: AHD/TVI In/Out: BNC sockets. Full HD: HDMI Socket. DVI: DVI-D Socket, VGA:15 pin Sub-D. Audio L & R In: Phono sockets, Out: Earphone: 3.5mm jack socket. DC input: 2.1mm socket. AC adaptor: IEC socket.

Standard accessories: AC adapter, AC Mains Lead, I/R Remote Control.

- All information is correct at time of going to press. Design and specification are subject to change without prior notice. E&EO