

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R26C enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

At a Glance

- Vandal resistant body, with a flush button;
- Wide-angle camera: 116° (H), 60° (V);
- PoE (IEEE802.3af, Power-over-Ethernet);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Complies with SIP standard for easy integration in every SIP capable PBXes;
- Complies with ONVIF standard for easy integration with any network surveillance system;



Physical & Power

- | | |
|---|---|
| • Front panel: Aluminum | • Speaker: 8Ω / 2W |
| • Camera: 2M pixels, automatic lighting | • Power out: 12V/400mA |
| • Button: 1 call button | • Ethernet port: RJ45, 10/100Mbps adaptive |
| • Light sensor: Support | • 802.3af Power-over-Ethernet |
| • Infrared sensor: Support | • 12V DC connector (if not using PoE) |
| • Wiegand port: Support | • Water-proof & Dust-proof: IP65 |
| • RS485 port: Support | • Installation: Flush-mounted or Wall-mounted |
| • RF card reader: 13.56MHz | • Flush-mounted DIM: 213x124x68mm |
| • Relays out: 2 | • Wall-mounted DIM: 190x110x40mm |
| • Inputs: 3 | • Working Humidity: 10~90% |
| • Microphone: -40dB | • Working Temperature: -20°C ~ +55°C |
| | • Storage Temperature: -40°C ~ +70°C |