

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R29S enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

At a Glance

- Enables audio and visual monitoring of doors/gates which increase security on residential or commercial premises;
- Allows both audio and video communication to an IP phone, mobile client, or softphone;
- Enables the ability to remotely control the door/gate;
- Presents information and user navigation options unique to your business;
- Eliminates the need for personnel to be physically stationed at the door/gate which improves productivity and frees them up to work on other things;
- Speeds response time to visitors, delivery and service personnel that require access;



Physical & Power

- | | |
|--|--|
| <ul style="list-style-type: none"> • Front panel: Aluminum • RAM / ROM: 2GB / 16GB • Display: 7 Inch IPS LCD • Screen: 7 Inch capacitive touch screen • Camera: 3M pixels, automatic lighting • Light sensor: Support • Infrared sensor: Support • Wiegand port: Support • RS485 port: Support • RF card reader: 13.56MHz & 125kHz • Relays In/out: 3/3 | <ul style="list-style-type: none"> • Microphone: -32dB • Speaker: 8Ω / 2W • Ethernet port: RJ45, 10/100Mbps adaptive • 802.3af Power-over-Ethernet • 12V DC connector (if not using PoE) • Water-proof & Dust-proof: IP65 • Installation: Flush-mounted & Wall-mounted • Flush-mounted DIM: 324x130x60mm • Wall-mounted DIM: 324x130x33mm • Working Humidity: 10~90% • Working Temperature: -20°C ~ +55°C • Storage Temperature: -40°C ~ +70°C |
|--|--|