



Product Image



Part Number

952/2.00 – Power Supply with Battery Charger - Output 24 V DC at 50W
909032059 – DIN Rail Power Supply with Battery Charger - Output 24 V DC at 50W

Dimensions

176mm x 50mm x 90mm

Operating Temperature

-20 to 50°C

Input Voltage

100-230V AC

Output Voltage

13.8V DC @ 3.3Amp

Frequency

50/60Hz

Efficiency

Efficiency Level VI (CEC)

Warranty

5 years against electronic failure

Certifications

CE, RoHS & WEEE compliant
CEC level 6 certified



Date of print/release: (July 2020)

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDX and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
Bredbury, Stockport, Cheshire, SK6 2SZ
customerservices@pacgdx.com | +44 (0) 161 406 3400
www.pacgdx.com