



Product Image



Part number	7257710 – Architect One RFID Mullion Reader
Dimensions	W 42 x H 112 x D 22mm
RFid Frequency	High Frequency (13.56 MHz: ISO14443A types A & B, ISO18092)
PAC ID Devices	PAC Ops™ Lite, PAC Ops™
Programmable Output Formats	PAC, PAC64
Maximum Read Range	60mm
Vandal Resistance	IK10 certification
Environment	IP65 – Indoor/Outdoor weather resistant
Power	9 – 15V DC, 130mA @ 12V DC
Operating Temperature	-30 to 70 °C
Operating Humidity	0-95% Relative Humidity
Audio/Visual Indicators	Audible Sounder and 2 x RGB LEDs (360 configurable colours)
Tamper Output	Accelerometer-based tamper detection system with key deletion option (patented solution)
Recommended Cabling	PAC output - 6 core 24 AWG alarm cable (unscreened)
Material	UL Rated ABS Plastic
Certification	CE / FCC/ UL compliant
Warranty	Lifetime against electronic failure

**Date of print/release: (July 2020)**

This document is provided by STANLEY Security or its affiliates ("STANLEY") for general information purposes only. STANLEY warrant the accuracy of the data as at the date of print/release, but it may be subject to change after such date. STANLEY will not be responsible for any loss or damage that may arise from reliance thereof. Copyright © STANLEY Security 2020. PAC, GDX and 3xLOGIC are the trade marks of STANLEY Security, Stanley Black & Decker, Inc., or their affiliates.

Ordering Information:

PAC Access Control, 1 Park Gate Close,
Bredbury, Stockport, Cheshire, SK6 2SZ
customerservices@pacgdx.com | +44 (0) 161 406 3400
www.pacgdx.com