

Belden Style

Data Cable

CQR

First choice for quality

A cable designed by CQR to meet all aspects of the European Construction Product Regulation (CPR) EN50575.

This cable has been independently tested and certified by an accredited test facility and has been awarded a CPR Euro classification.




CQR offer the Installer, Specifier and End User a quality cabling solution and piece of mind that the product will perform to specification in the event of a fire.

DoP Certificates available online for download



- Typically used for security and access control RS-232, RS485 data transfer
- 7 x 0.25mm Tinned Copper
- Sheathed in PVC or LSZH
- Screened Pairs
- Manufactured to BS4737-3.30:2015 Type 2 (PVCV), Type 1 (LSZH)
- Fully compliant with EN50575 'CPR'

Available Cores



Product codes

| Code | Description |
|-------------------|--|
| CABTP2X2/GY/100 | Belden Style 8723 Twisted Pair 100m Grey |
| CABTP2X2/WH/100 | Belden Style 8723 Twisted Pair 100m White |
| CABTPHF2X2/WH/100 | Belden Style 8723 HF Twisted Pair 100m White |
| CABTP3X2/1C/AB | Belden Style 8777 Twisted Pair 100m Box |
| CABTPHF3X2/1C/AB | Belden Style 8777 HF Twisted Pair 100m Box |
| CABTPHF3X2/5R/AB | Belden Style 8777 HF Twisted Pair 500m Reel |

Other cable lengths and colour available
See www.cqr.co.uk for details

Technical data

| | |
|---------------------|----------------------|
| Core: | 7 x 0.25mm |
| Resistance: | 50.1 Ohms/Km |
| AWG: | 22 |
| Conductor Material: | Tinned Copper |
| Conductor area: | 0.344mm ² |
| Max voltage: | 50 volts |
| Sheathing: | LSZH or PVC |
| Core insulation: | LSZH |
| Euroclass Rating: | E _{ca} |
| SCREENED CABLE | |
| Drain wire: | Soft tinned copper |
| Screen: | Alu/Polyester Foil |

rev. 4-11/2020



www.cqr.co.uk

info@cqr.co.uk

Sales: +(0)151 606 1000 Tech: +(0)151 606 6311

CQR Security Ltd, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

Over 30 Years experience of alarm cable manufacturing in the United Kingdom

