### **Product data sheet**



# AS272

## Indoor siren, 2 tones - without flash

The AS270 series of sirens is ideal for use as an internal alarm sounder for residential and industrial alarm applications.



#### **Details**

- Low current consumption
- 2 tones
- Pry-off & opening tamper protection
- Easy to install (1 fixing screw for cover)
- Vertical or horizontal mounting
- Self activating version available
- ANPI, NFA2P and VdS version available

# AS272

## Indoor siren, 2 tones - without flash

### **Technical specifications**

General	
Accessory group	Siren
Туре	Indoor siren
Sounder output (dB @ distance)	101 dB at 1 m (typical)
Electrical	
Operating voltage	10 to 14.2 V
Power supply value	10.0 to 14.2 VDC
Current consumption	120 mA at 12 VDC (typical)
Battery capacity	280 mAh, 10.8 V NiCd
Physical	
Physical dimensions	155 x 114 x 44 mm
Net weight	220 g
Colour	White
Material	ABS
Environmental	
Operating temperature	-25 to +55°C
IP rating	IP315
Standards & regula	ation
Certification	CE

As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

