
Belden equivalents

**TITLE:**
Overall Foil Screened Pairs LSZH

**CODE:**
OSP3-LSZH-D-GRY-100

**DESCRIPTION:**
OSP3 3pr 24AWG Overall Foil Screen 600V Grey LSZH Dca

- Additional screening makes this cable suitable to be installed in areas where protection from electrical interference is required
- A general purpose small diameter cable
- Low Smoke Zero halogen
- CPR Rated: Dca -s:2 -a:1 -d:2
- Supplied as 100m










Belden equivalents

# Product Specification

25-YEAR WARRANTY

UK CA

## Cable Construction

| | |
|---|---|
| Cable Construction | 3 Pairs |
| CPR | Dca -s:2 -a:1 -d:2 |
| Conductor | Tinned Copper |
| Conductor 2 | N/A |
| Conductor 3 | N/A |
| Conductor Diameter (mm) | 0.19 ±0.008 x 8 |
| Inner Conductor | Tinned Copper |
| Stranded Diameter (mm) | 0.62 |
| Overall Diameter (mm) | 5.70 ±0.20 |

## Insulation

| | |
|---|---|
| Insulation | LSZH |
| Insulation Colour | Red,Black;White,Black;Green,Black |
| Insulation Resistance @20°C | >200MO/km |
| Insulation Thickness (mm) | 0.28 |

## Outer/Jacket Specification

| | |
|---|---|
| Outer Jacket | LSZH |
| Outer Jacket Colour | Grey RAL 7042 |
| Inner Jacket | N/A |
| Inner Jacket Colour | N/A |
| Inner Jacket Diameter (mm) | N/A |
| Inner Jacket Thickness (mm) | N/A |
| Jacket | LSZH |
| Overall Colour | Grey |
| Overall Diameter (mm) | 5.70 ±0.20 |
| Jacket Colour | Grey RAL 7042 |
| Jacket Thickness (mm) | 0.70 |
| Nylon Rip-Cord | Yes |

## Electrical Characteristics

| | |
|---|---|
| Insulation Resistance @20°C | >200MO/km |
| Max Conductor DC resistance @ 20°C | <79.00O/km |
| Outer Conductor DC resistance @ 20°C | ≤58.0 Ω/km |
| Rated Temperature (°C) | -40°C to 70°C |
| Rated Voltage (V) | 600V |
| Impedance | 75Ω Nominal |
| Capacitance | C:C 98 pF/m Nom; C:P 180 pF/m Nom |

Belden equivalents

# MORE INFORMATION:

| EURO CLASS (ca:cable) | CLASSIFICATION CRITERIA: FIRE RATING | CLASSIFICATION CRITERIA: SFX COMMENT |
|---|---|---|
| Reaction to Fire BS EN ISO 1716 | | |
| $A_{ca}$ | Does not contribute to the fire | Due to availability, it will be almost impossible for a cable to meet Aca, so they should only be specified with extreme caution. |
| Reaction to Fire BS EN 50399 | | |
| $B1_{ca}$ | Minimum contribution to the fire | It's highly unlikely the commonly-used cables will be classified to Class B1ca. |
| $B2_{ca}$ | Combustible, low flame spread & heat release contribution to the fire | Similar to Class Cca, although a lower acceptable heat release rate and burn measurement. In practice, this is likely to be the highest class cables will meet. |
| $C_{ca}$ | Combustible, moderate flame spread & heat release | This is a more rigorous test than Class Dca, this is widely accepted across Europe as the 'go to' classification, but be aware, many cables do not meet Class Cca though availability is improving. |
| $D_{ca}$ | Combustible, moderate flame spread & heat release | This classification has relatively little use or acceptance within specifying/contracting organisations. This is because no large scale fire growth is measured. |
| Reaction to Fire BS EN 60332-1-2 | | |
| $E_{ca}$ | Combustible, limited fire spread of less than 425mm | A basic test for vertical flame propagation for a single insulated wire or cable using a 1 KW pre-mixed flame. Note: This test does not measure heat release, toxic fumes or smoke. |
| $F_{ca}$ | Combustible, fire spread of more than 425mm | Cables classified to Class Fca may have high levels of flammability due to the materials they are made of. This does not mean that the cable cannot be used, it is more likely to be used external. |

## CPR GUIDE

Securi-Flex®

SUBCLASSIFICATIONS FOR EUROCLASSES Bca to Dca

| (S) SMOKE PRODUCTION | (D) FLAMING DROPLETS | (A) SMOKE ACIDITY |
|---|---|---|
| BS EN 50399/BS EN 61034-2 | BS EN 50399 | BS EN 60754-2 |
| s1a: s1 + transmittance >=80% (BS EN 61034-2) | d0: No fall of droplets or flaming particles, times for 1200 seconds | a1: Very low acidity (conductivity <2.5 µS/mm & pH >4.3) |
| s1b: s1 + transmittance >=60% <80% (BS EN 61034-2) | | |
| s1: Low production of slow propagation of smoke | d1: Fall of droplets or flaming particles that persist for less than 10 seconds, timed for 1200 seconds | a2: low acidity (conductivity <10 µS/mm & pH >4.3) |
| s2: Intermediate production & propagation of smoke | | |
| s3: None of the above | d2: None of the above | d2: None of the above |

**Visit us online:**
**www.securiflex.co.uk**

SFX® The Trusted Cable Brand

Classes A to E have to be tested by an independent authorised laboratory.
Most cables will fall into classes B2ca to Eca.
For a cable to meet Aca, B1ca, B2ca or Cca, there also needs to be regular on-going factory audits.

## OUR OPERATING TEMPERATURE RANGE GUIDE

