Essentials by vista


In Partnership with Securi-Flex®

OSC8-LSZH-B2-GRY

OSC8 8 Core 24AWG Overall Foil Screen 600V Grey LSZH (9538) CPR:B2ca -s:1 -a:1 -d:0

Import / Export Commodity Code 8544499590 / 85444995





Cable Construction	8 Cores
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7(0.22mm²)
Stranded Diameter (mm)	0.22
Insulation	LSZH
Insulation Thickness (mm)	0.3
Insulation Diameter (mm)	1.20 ±0.10
Insulation Colour(s)	Red,Black,White,Green,Blue,Brown,Orange,Yellow
Al-PET Shield	>=115%
Drain Wire	
Drain Wire Conductor	Tinned Copper
Drain Wire Conductor Diameter (mm)	0.19 ±0.008 x 7
Jacket	LSZH
Jacket Thickness (mm)	0.70
Overall Diameter (mm)	5.20 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSC8 8x24AWG 600V Overall Screened LSZH RoHS2 B2ca (PO) (m)
Reaction to Fire	B2ca -s1a -a1 -d0
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<90.00Ω/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control, instrumentation, panel wiring and RS232 applications.